

MasterColor CDM ED17 Elite

MasterColor CDM 70W ED17 ELITE

MasterColor Ceramic Metal Halide ED-17 Elite lamps provide excellen lumen maintenance and outstanding performance over time in the familiar ED-17 lamp shape.

Product data

• General Characteristics

Base Medium [Single Contact Medium Screw] Base Information

Brass [Brass Base] Bulb **ED17 Bulb Material** Hard Glass **Bulb Finish** Clear

Operating Position Universal [Any or Universal (U)] Main Application General and Street Lighting

RatedAvgLife(See 16000 hr

Family Notes)

• Light Technical Characteristics

Color Code 930 [CCT of 3000K] Color Rendering 88 (min), 90 (nom) Ra8

Index

Color Designation Warm White 2900 K Color Temperature Color Temperature 2900 K

technical

Initial Lumens 6700 Lm Luminous Efficacy 95 Lm/W

Lamp EM

95 % Lumen Maintenance -10% life Lumen Maintenance -90 %

40% life

Design Mean Lumens 5360 Lm

Chromaticity Coor-

0.433 (min), 0.442 (nom), 0.451 (max)

dinate X

Chromaticity Coor-0.394 (min), 0.400 (nom), 0.406 (max)

dinate Y

• Electrical Characteristics

Watts 70 W

100 V Lamp Voltage 0.92 A Lamp Current 10 (max) s Ignition Time Re-ignition Time 8 (max) min

[min]

• Environmental Characteristics

Mercury (Hg) 8.0 (max) mg Content

Picogram per Lumen 88.6 p/LuHr

Hour

• UV-related Characteristics

Damage Factor D/fc PET (NIOSH) 1045 h500lx UV A 3.5 mW/cm2 UV B 0 mW/cm2 UV C 0 mW/cm2

• Luminaire Design Requirements

Cap-Base Tempera-190 (max) C ture

Bulb Temperature 400 (max) C

Product Dimensions

3.39 in Light Center Length

Max Overall Length 5.438 (max) in

(MOL) - C

Diameter D 2.125 in



MasterColor CDM ED17 Elite

Footnotes

Footnotes HID 902 [Exclusive to Philips Lighting

Company.]

• Product Data

Product number 423707

Full product name MasterColor CDM 70W ED17 ELITE

 Pieces per Sku
 1

 Skus/Case
 12

 Bar code on pack
 46677423704

 Bar code on case
 50046677423709

 Logistics code(s)
 928601173801

 eop_net_weight_pp
 0.001 kg

Short product name

remain for more than a few minutes unless adequate shielding or other safety precuations are used. Certain lamps that will automaticallly extinguish when the outer envelope is broken or punctured are commercially available." This lamp complies with FDA radiation performance standard 21 CFR subchapter J. (USA:21 CFR 1040.30 Canada: SOR/DORS/80-381)

MHC70/U/MP/3K ELITE


Warnings and Safety

• R "WARNING: These lamps can cause serious skin burn and eye inflammation from short wave ultraviolet radiation if outer envelope ot the lamp is broken or puntured. Do not use where people will

Dimensional drawing

MasterColor CDM 70W ED17 ELITE

Product	C (Max)	D (Norm)
MHC 70W/930 E26 ED17 CL U ELITE	5.438	2,125





E26



Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips Electronics N.V. or their respective owners.