

141

Plated

papcolloy HIGH STRENGTH UNI-RODS®

UNC - Unified National Coarse Thread

UNF - Unified National Fine Thread

B7

Alloy Steel

Threaded
Full Length

Gold Zinc Dichromate Plated

High strength continuous threaded rod to ASTM A-193 B7 Specification. Heat treated. Chrome-moly steel, tensile strength exceeds 125,000 psi. Used for vehicles, construction, mining, chemical and petroleum equipment. Temperature service range from -150°F to +850°F.

LIST PRICE PER EACH

UNC COARSE THREAD 36" LENGTHS					UNF FINE THREAD 36" LENGTHS				
Size No.	Dia. Inches	PACKAGED		Approx. Weight 100 Pcs.	Size No.	Dia. Inches	PACKAGED		Approx. Weight 100 Pcs.
		Coarse Thread 141	Pkg Qty				Fine Thread 141	Pkg Qty	
-550	1/4	\$9.43	5	36	-570	1/4	\$10.95	5	36
-551	5/16	10.90	4	59	-571	5/16	12.43	4	59
-552	3/8	11.84	3	88	-572	3/8	15.18	3	88
-553	7/16	13.20	2	120	-573	7/16	17.39	2	120
-554	1/2	14.35	2	159	-574	1/2	18.68	2	159
-555	9/16	16.46	2	206	-	-	-	-	206
-556	5/8	20.95	2	253	-576	5/8	25.65	2	253
-557	3/4	29.55	2	370	-577	3/4	34.65	2	370
-558	7/8	40.13	1	511	-578	7/8	48.99	1	511
-559	1	52.39	1	668	-579	1	65.16	1	668
-561	1-1/8	69.01	1	843	-580	1-1/8	79.86	1	843
-563	1-1/4	84.45	1	1060	-581	1-1/4	104.11	1	1060
-565	1-1/2	134.99	1	1536	-582	1-1/2	165.49	1	1536

141

Plated

METRIC UNI-RODS®

ISO Coarse Thread

FULLY THREADED STEEL RODS

Bright Zinc Plated

1 METRE LENGTHS

LIST PRICE PER 100 PIECES

PLATED - 1 Metre LENGTHS									
Size No.	Dia. (mm)	PACKAGED		Approx. Weight 100 Pcs.	Size No.	Dia. (mm)	PACKAGED		Approx. Weight 100 Pcs.
		141	Pkg Qty				141	Pkg Qty	
-706	M6x1.0	\$286.61	10	50	-710	M10x1.5	\$738.24	10	140
-708	M8x1.25	442.94	10	90	-712	M12x1.75	981.43	5	200

141


Plated

COUPLING NUTS

FULL THREAD

UNC - Unified National Coarse Thread

Bright Zinc Plated



LIST PRICE PER 100 PIECES

Size No.	Bolt Dia. Inches	CASE			BULK			Dimensions	
		Coarse Thread 141	Pkg Qty	Case Qty	Coarse Thread B141	Bulk Qty	Approx. Wt. 100 Pcs.	Across Flats	Thickness
-914	1/4	\$10.80	50	1200	\$10.04	1200	3	7/16	7/8
-916	5/16	25.39	25	600	23.63	700	7	1/2	1-3/4
-918	3/8	33.31	25	500	30.74	650	9	9/16	1-3/4
-920	7/16	42.97	25	450	38.12	500	10	5/8	1-3/4
-922	1/2	61.49	25	300	56.42	350	15	3/4	1-3/4
-924	5/8	128.04	15	150	116.88	160	31	15/16	1-3/4
-926	3/4	198.40	15	100	180.56	120	42	1-1/8	2-1/4
-928	7/8	245.98	10	80	228.02	100	58	1-1/4	2-1/2
-930	1	194.39	10	80	182.33	100	46	1-1/4	2-1/2