



Commercial Specification Grade Straight Blade Power Devices



**3-Pole, 4-Wire Grounding
NEMA 14-20,14-30,
20A 125/25V,
30A 125/250V**

Power Devices

FEATURES

- Heavy gauge galvanized steel mounting strap for corrosion resistance.
- Receptacles for use with copper or aluminum wire.
- Surface receptacles have patented lay-in terminals and accept up to #4 wire.
- Universal plugs include blades for 30A or 50A configurations.
- Surface receptacles 0.75" (19.05mm) and 1" (25.4mm) concentric knockouts and adjustable cord clamp allow for wiring from bottom or back.
- Flush receptacles fit one or two gang enclosures.
- High strength glass reinforced nylon body resists breakage in high abuse areas for Catalog No. 5744N.

G-27 Straight Blade Receptacles



NEMA 14-20 Rating 20A 125/250V

Receptacles

Description	Color	Catalog No.
Single, Phenolic, Back and Side Wired	Black	5759*

*UL498 Listed (File No. E140596)

NEMA 14-30 Rating 30A 125/250V

Receptacles

Description	Color	Catalog No.
Surface	Black	1225
On 4.6875" (119.06mm) Steel Cover	Black	1167
Flush	Black	5744N
Flush	Black	1257
Panel Mount	Black	57

Plug

Description	Cord Diameter	Color	Catalog No.
Angle Universal - PVC	1.125" (28.575mm)	Black	S21

Wallplate Guide for Power Devices

Power Device Catalog No.	Wallplate Catalog No.
1257	39CH, 68, 2068, 2168, 93221, 93227, 5068, PJ724, PJ703
5744N	69, 5169, 93223

TESTING & CODE COMPLIANCE

- UL Listed, Receptacles: file no. E15058; Plugs: UL and cUL, file no. E15012.
- CSA (file no. 6914 (6233-01)).
- Meets all CSA requirements, C22.2 no. 42.
- NOM Certified.

MATERIAL CHARACTERISTICS

Plugs: PVC. Flush Receptacles: Phenolic; Surface Receptacles: PVC, Panel Mount Receptacles: Phenolic. Temperature Rating: -20°C (without impact) to 75°C max. continuous. 5744N: -40°C (without impact) to 105°C max. continuous.



14-20R



14-20P



14-30R



14-30P