



INDUSTRIAL
COMMERCIAL
RESIDENTIAL


A-21 STRAIGHT BLADE RECEPTACLES

TESTING & CODE COMPLIANCE


- UL Listed:
1263, 1231, 1233:
(file no. E15058).
CSA file 6914
(6233-01).
- 83 & 41:
UL (file no. E15012),
CSA file 2081
(6221-02).
- 5716N to 498,
meets UL Federal
Spec. WC-596
(file no. E2369).
- CSA Certified to
C22.2 no. 42.
- NOM Certified,
except as noted.

MATERIAL CHARACTERISTICS

Temperature Rating:
-20°C (without
impact) to 75°C
max. continuous.
5716N: V2 rated;
-40°C (without
impact) to 105°C
max. continuous.



1263




1264



1231



41



5716N

Commercial Specification Grade Straight Blade Power Devices

2 Pole, 3 Wire Grounding
NEMA TT-30, 5-30
30A 125V

Power Devices

FEATURES

- Heavy gauge steel mounting strap zinc-plated for corrosion resistance.
- Receptacles for use with copper or aluminum wire.
- Surface receptacles have patented lay-in terminals and accept up to #4 wire.
- Universal plugs include blades for 30A configurations.
- Surface receptacles 0.75" (19.05mm) and 1.0" (25.4mm) concentric knockouts and adjustable cord clamp allow for wiring from bottom or back.
- Flush receptacles fit one or two gang enclosures.
- High strength glass reinforced nylon body resists breakage in high abuse areas for Catalog No. 5716N.

NEMA TT-30 Rating 30A 125V

Receptacles

Description	Color	Catalog No.
Flush	Brown	1263*
Panel Mount (by special order only)	Brown	U1263*

*Not NOM

Plugs

Description	Color	Catalog No.
Angle Travel Trailer	Black	83

Adapter

Description	Color	Catalog No.
Travel Trailer Plug to Female Receptacle - 15A or 20A 125V NEMA 5-15R or 5-20R	Black	1264†

†1264 is not CSA approved

NEMA 5-30 Rating 30A 125V

Receptacles

Description	Color	Catalog No.
Surface	Black	1231†
Flush	Black	5716N
Flush	Brown	1233

Plugs

Description	Color	Catalog No.
Angle Universal - Vinyl	Black	41

†Not UL Listed



TT-30R



TT-30P



5-30R



5-30P