Wiring Devices | Combination Devices

Combination USB Charger with Tamper Resistant Receptacle

2-Pole, 3-Wire Grounding 15A, 125V, 5V DC 700MA 15A, 125V, 5V DC 2100MA 20A, 125V, 5V DC 2100MA



TR7740



Features

- Standard AC receptacle with two USB charging ports for conveniently charging most electronic components
- Dual USB charging ports charge most compatible electronic devices that charge via a 5V power adapter
- LED indicator light
- Three (3) pre-stripped 6" wire leads for line, neutral and ground for quick and easy installation (TR7745 and TR7746 only)
- Tamper Resistant Shutters provide compliance with 2011 NEC® Article 406.12 that states that all 15A and 20A, 125V receptacles installed in dwelling units must be tamper resistant
- Automatic grounding system eliminates need for bonding jumper in grounded metal enclosure and provides redundant measure of ground continuity where jumper is used

- Thermoplastic top and back-body are virtually unbreakable to deliver years of durable performance
- Steel mounting strap is zinc-plated for added corrosion resistance
- Convenient patented built-in wire strippers speeds installation
- Backwire clamps on side terminals provide for easy installation of #12 and #14 AWG wire (TR7740)
- Triple wipe blade contacts and double wipe ground contacts to insure long-term plug retention
- Replaces a standard duplex receptacle

Combination USB Charger with TR Receptacle (10) ISB Charger with TR Receptacle						
Α	R V/AC	ating MA	V/DC	Description	Color Suffix	Catalog No.
15	125	700	5	Combination USB Charger with TR Receptacle	A, BK, LA, V, W	□ TR7740
15	125	2100	5	USB Charger with TR Duplex Receptacle, Wire Leads	A, BK, LA, V, W	□ TR7745
20	125	2100	5	USB Charger with TR Duplex Receptacle, Wire Leads	A, BK, LA, V, W	□ TR7746

cULus Listed UL 498 and UL1310; NOM certified

Color Ordering Information:

For ordering devices, include Catalog No. followed by the Color Suffix: A (Almond), BK (Black), LA (Light Almond), V (Ivory), W (White)



Dimensional Information: B-68 Specification Information: Please visit www.cooperwiringdevices.com. Specifications and availability are subject to change without notice.

