

# **Power devices**

# Range & dryer power receptacles

#### **Product description**

3-pole, 3-wire non-grounding 30A, 125/250V/AC 50A, 125/250V/AC

#### **Design features**

- For replacement use in older homes with 3-wire range and dryer connection points
- Heavy gauge galvanized steel mounting strap for corrosion resistance
- Flush receptacles fit one-gang or two-gang enclosures





10-30R





14-30R 14-

- For use with copper or aluminum wire
- Surface receptacles have patented lay-in terminals that accept up to #4 AWG wire
- Surface receptacle backs feature concentric knockouts and an adjustable cord clamp to allow wiring from back or bottom



32B



112



1258

### Flush power receptacles





Ra	ating				
Α	V/AC	Description	Color	Catalog no.	_
30	125/250	NEMA 10-30R flush mount dryer power receptacle, matching plug S80	В	□ 38B	•
50	125/250	NEMA 10-50R flush mount range power receptacle, matching plug S80	В	□ 32B	•

cULus Listed to UL498 & UL943, file no. E60120; NOM certified

### Surface power receptacles





Ra A	ating V/AC	Description	Color	Catalog no.	<b>.</b>
30	125/250	NEMA 10-30R flush mount dryer power receptacle, matching plug S80	BK	□ 125	•
50	125/250	NEMA 10-50R flush mount range power receptacle, matching plug S80	BK	□ 112	•

Listed to UL498, file no. E15058; CSA certified to C22.2, no. 42; NOM certified

#### Flush power receptacles





Ra	ating		Color	Catalog no.	
Α	V/AC	Description			
30	125/250	NEMA 14-30R flush mount dryer power receptacle, matching plug S21	BK	□ 1257	•
50	125/250	NEMA 14-50R flush mount range power, matching plug S21	BK	□ 1258	•

Listed to UL498, file no. E15058; CSA certified to C22.2, no. 42; NOM certified

## Color ordering information:

B (Brown), BK (Black)





Dimensional information: B-70 Specification information: Please visit www.cooperwiringdevices.com Compliances, specifications and availability are subject to change without notice.



Indicates NAFTA compliant - Page F-21