


Industrial grade 30A locking devices

Product description


3-pole, 4-wire grounding
30A, 3Ø 250V/AC
NEMA L15-30




AHL1530P



AHL1530C



AHL1530R



AHL1530FI

Industrial grade plugs & connectors



| Rating | V/AC | NEMA | Description | Cord diameter | Color | Plug catalog no. | Connector catalog no. | |
|--------|------|--------|-----------------------------|----------------------------|--------|-----------------------------------|-----------------------------------|--|
| 30 | 250 | L15-30 | 3Ø ultra grip straight body | 0.38-1.16" (9.5-29.4mm) | BK & W | <input type="checkbox"/> AHL1530P | <input type="checkbox"/> AHL1530C | |

Industrial grade receptacles



| Rating | V/AC | NEMA | Description | Color | Single receptacle | |
|--------|------|--------|------------------------|-------|------------------------------------|--|
| 30 | 250 | L15-30 | 3Ø standard industrial | BK | <input type="checkbox"/> AHL1530R | |
| | | | 3Ø isolated ground | RN | <input type="checkbox"/> IGL1530R* | |

*Not Fed Spec

Industrial grade flanged inlets & outlets



| Rating | V/AC | NEMA | Description | Color | Flanged inlet | Flanged outlet | |
|--------|------|--------|------------------------|--------|------------------------------------|---|--|
| 30 | 250 | L15-30 | 3Ø standard industrial | BK | <input type="checkbox"/> AHL1530FI | — | |
| | | | 3Ø standard industrial | BK & W | — | <input type="checkbox"/> AHL1530FO ¹ | |

¹Only UL Listed and CSA Certified

Accessories for L15-30 locking devices

| Description | Catalog no. | |
|--|-------------------------------|--|
| Neoprene weather protective boot for 4-W & 5-W plugs | <input type="checkbox"/> BL1 | |
| Neoprene weather protective boot for 4-W & 5-W connectors | <input type="checkbox"/> BL2 | |
| Diecast aluminum single receptacle cover, vertical mount, for FS/FD boxes | <input type="checkbox"/> 7420 | |
| Glass-filled nylon flanged inlet/outlet cover, vertical mount, for 30A devices | <input type="checkbox"/> WP2 | |



BL1

BL2

7420

WP2

Dimensional information:

C-76-C-78

Plug & connector specification information:

L15-30: C-84

Receptacle specification information:

L15-30: C-87

Isolated ground L15-30: C-87

Flanged inlet & flanged outlet specification information:

L15-30: C-89

Color information:

BK (Black), RN (Orange), W (White)



Compliances, specifications and availability are subject to change without notice.

Indicates NAFTA compliant - Page Q-32

RoHS compliant - Page Q-32