

Ceiling receptacle lampholders

Product description

Medium base
660W, 125V/AC
660W, 250V/AC
600W, 250V/AC

Design features

- Mounts on 4" (101.6mm) outlet boxes with breakout for 3.25" (82.5mm) box mounting
- Leads are 6" (152.4mm) 221°F (105°C) insulated stranded #16 AWG, stripped 0.75" (19.0mm)
- Top wire versions have terminal screws backed out—ready for wiring—without removing interior
- Push wire terminals are top wired with two push-in terminals and two screw terminals for continuous wiring
- Pull chain devices include ball chain, 3' (0.9m) of cord, connector and end bell
- Porcelain models made of high-strength insulator porcelain; pull chain versions feature removable interiors
- Plastic models made with high-temperature thermoset plastic to reduce breakage



667



669



S788W



S1174W

Porcelain ceiling lampholder



A	Rating		Description	Color	Catalog no.
	V/AC	W			
15	125	660	Two-piece, with NEMA 1-15P 2P, 2W outlet 2 screw terminals, pull chain switch, top wire	W	□ 669
15	125	660	Two-piece, with NEMA 5-15P 2P, 3W outlet 2 screw terminals, pull chain switch, top wire	W	□ 667
	250	660	One-piece, with feed-through, 4 screw terminals, keyless switch, top wire	W	□ 604
	250	660	Two-piece, with feed-through 4 screw terminals, pull chain switch, top wire	W	□ 659

cULus Listed to UL 496, file no. E7430; NOM certified

Plastic ceiling lampholder



Rating		Description	Color	Catalog no.	
W	V/AC				
600	250	Two-piece, push wire/top wire, pull chain switch	W	□ S759W-CD	
600	250	Two-piece, 6" (152.4mm) wire leads, pull chain switch	W	□ S788W	
660	250	Two-piece, with 15A 125V/AC NEMA 1-15P 2P, 2W outlet push wire/top wire, pull chain switch	W	□ S860W	
660	250	Two-piece, with 15A 125V/AC NEMA 5-15P 2P, 3W outlet push wire/top wire, pull chain switch	W	□ S865W	
660	250	One-piece, 4 top wire screws, keyless switch	W	□ S1174W	•
660	250	One-piece, 6" (152.4mm) wire leads, keyless switch	W	□ S1174-6W	•
660	250	Two-piece, push wire/top wire, keyless switch	W	□ S768W	
660	250	Two-piece, 6" (152.4mm) wire leads, keyless switch	W	□ S768-6W	

cULus Listed to UL 496, file no. E7430; NOM certified

Color ordering information:

W (White)



(White)

Dimensional information: B-71 **Specification information:** Please visit www.cooperwiringdevices.com
Compliances, specifications and availability are subject to change without notice.

Indicates NAFTA compliant - Page F-21