



CRC Power Lube® High Performance Lubricant is a multi-purpose lubricant with PTFE used to provide long lasting lubrication and protection against friction, wear and corrosion.

LUBRICANTS

2-26® MULTI-PURPOSE PRECISION LUBRICANT

- Drives out moisture leaving a thin, long lasting film to protect against corrosion
- Excellent for use around modern plastics and insulators
- Plastic Safe
- Prevents corrosion by displacing moisture
- Restores resistance values, helps stop current leakage
- Helps restore water damaged electrical equipment
- Convenient 360 spray valve - can be sprayed from any position

Part Number	Container Size	Units per Case
72005	312 g Aerosol	12

POWER LUBE® W/PTFE HIGH-PERFORMANCE LUBRICANT

- High performance, multi-purpose lubricant with the benefits of PTFE
- Withstands extreme load carrying situations
- Displaces moisture and seals out corrosion
- Surpasses 4,500 lbs on Falex Load Test (ASTM D-3233)

Part Number	Container Size	Units per Case
73045*	312 g Aerosol	12

DRY MOLY LUBE

- Specially formulated dry film lubricant incorporating a concentrated dispersion of molybdenum disulfide (MoS₂)
- Lowers friction and prevents galling
- Helps to reduce torque and energy consumption
- High anti-friction and anti-seizure properties
- Lubricant resists high temperatures (up to 343°C), high pressure, water and chemical attack
- Non-conductive
- Harmless to most plastics, rubbers and metals

Part Number	Container Size	Units per Case
73084*	312 g Aerosol	12

WHITE LITHIUM GREASE

- High-purity, high-quality, NLGI Grade 2 white lithium-based aerosol grease
- Excellent as a break-in lubricant for machinery, tools and equipment
- Excellent heat and water resistance
- Contains rust and oxidation inhibitors for superior metal protection
- Protects with a tough, high viscosity film
- White color allows for easy visual inspection

Part Number	Container Size	Units per Case
73200*	284 g Aerosol	12

HEAVY DUTY CLEAR PENETRATING GREASE

- High tack, clear lubricating gel provides superior lubrication; contains PTFE
- Resistant to acids, alkalis, salt, oxidation, weather and steam
- Extends the operating service life of equipment and reduces wear, galling and scarring
- Withstands high temperature (up to 260°C) and pressure
- Waterproof and prevents corrosion
- Penetrates to form a thick, long-lasting film

Part Number	Container Size	Units per Case
73156*	369 g Aerosol	12

DI-ELECTRIC GREASE

- Unique, non-curing silicone compound used for electrical sealing, lubricating, protecting and insulating
- Waterproofs electrical connections and components to protect against arcing due to moisture and other contaminants
- Improves electrical performance during adverse conditions such as rain, fog, salt spray and temperature extremes
- Excellent lubricant for rubber and plastic parts
- Wide temperature range (-56°C to 204°C)

Part Number	Container Size	Units per Case
73082*	284 g Aerosol	12
75106	94 g Pressurized Tube	12

NICKEL ANTI-SEIZE AND LUBRICATING COMPOUND

- Protects metal-to-metal applications from seizing and galling caused by high temperatures, heavy loads, vibration, chemicals and corrosion
- High temperature resistance protects parts up to 1315°C
- Electrically conductive – does not insulate and interrupt current flow
- Does not compromise integrity of soft metals
- Safe for use on both ferrous and non-ferrous metals
- Will not harden – heat aging won't affect lubricity of product
- Resistant to mild detergents and alkaline wash to protect against rust and corrosion

Part Number	Container Size	Units per Case
72911	227 g Brush-Top Bottle	12

*This product is labeled extremely flammable. Read and observe the special usage warning on the label. Do not apply while equipment is energized.

CRC Canada Co. • Sales and Technical Support T. 905-670-2291 • F. 905-670-5941 • sales@crc-canada.ca
www.CRC-Canada.ca • Products manufactured in an ISO-9001:2008 Certified Manufacturing Facility.