

FIBERGLASS

300 lbs. load capacity*
TYPE IA
*Includes weight of user and tools.

EXTENSION LADDER FE3200 SERIES

EXTENSION LADDERS



FE3220

QuickLatch®
Patent # 5429207

Steel swivel safety shoe w/ metal shield

Outside slide guides

D-shaped rungs

Mar-resistant rail end caps

ALSO AVAILABLE WITH...



L-3022-PT SERIES

Patent #7,753,170

A multifunctional top designed to increase productivity.

- **CORNER GRIP**
The V-shape design provides greater stability on corners.
- **POLE GRIP**
The V-shape design with rubber tread makes it ideal for working against poles or trees. The tool slots provide the option for lashing the ladder to the pole or tree.
- **INTEGRATED BUMPER**
Soft non-marking/non-marring rubber tread protects the work surface.
- **WIDER DESIGN**
Wider design provides greater stability and 700% more contact area on flat surfaces.
- **WORK TRAY**
Non-conductive molded work-tray with convenient handyman's tool slots.

EXTENSION LADDERS WITH PROTOP™					
MODEL	TOTAL LENGTH	LENGTH EACH SECTION	MAX. EX. LENGTH	APPROX. WT. (LBS)	APPROX. CUBES
L-3022-20PT	20'	10'	17'	42	8.6'
L-3022-24PT	24'	12'	21'	52	10.2'
L-3022-28PT	28'	14'	25'	58	10.6'
L-3022-32PT	32'	16'	29'	70	12'

MODEL	TOTAL LENGTH	LENGTH EACH SECTION	MAX. EX. LENGTH	APPROX. WT. (LBS)	APPROX. CUBES
FE3216*	16'	8'	13'	30	6.5'
FE3220	20'	10'	17'	42	8.6'
FE3224	24'	12'	21'	52	10.2'
FE3228	28'	14'	25'	58	11.9'
FE3232	32'	16'	29'	70	12.6'
FE3236**	36'	18'	32'	79	15.8'
FE3240**	40'	20'	35'	93	17.5'

*Does not include rope and pulley.
** 250 lb. Type I rated.

SIZES	RAIL DEPTH	STACK HEIGHT	INSIDE WIDTH		OUTSIDE WIDTH	
			BASE	FLY	BASE	FLY
16'-28'	3 1/4"	6 1/4"	14 1/16"	13 1/16"	17 1/16"	16 1/16"
32'-40'	3 5/16"	6 1/4"	15 5/16"	14 5/16"	17 1/16"	16 1/16"

SINGLE LADDERS - FE3100			
MODEL	TOTAL LENGTH	APPROX. WT. (LBS)	APPROX. CUBES
FE3108	8'	16	3'
FE3110	10'	21	5.3'
FE3112	12'	25	4.8'
FE3114	14'	28	5.6'
FE3116	16'	36	6.7'
FE3118	18'	41	7.5'
> FE3120	20'	45	11.4'

> Special order item.

SIZES	RAIL DEPTH	OUTSIDE WIDTH	INSIDE WIDTH
8'-14'	3 1/4"	17 1/16"	14 1/16"
16'-20'	3 5/16"	17 1/16"	15 5/16"

LOUISVILLE™



ANSI
Meets or exceeds requirements of American National Standards Institute
ANSI A14.5

