

Aluminum Alloys



FILLER METALS

Precision made on the latest equipment from materials of the finest quality. UNIBRAZE spooled aluminum wire is triple degreased to provide the highest degree for cleanliness and luster. The UNIBRAZE “shaved finish” produces absolute uniformity in diameter along with excellent surface smoothness so as to guarantee uninterrupted feeding in automatic and semi-automatic operations.

Rigid quality controls in every stage of manufacture and packaging assure maximum welding and brazing efficiency and trouble free welding results. Unique cleaning methods remove all traces for oxides, lubricants and acids. Special packaging maintains absolute cleanliness and prevents contamination.

With state of the art, proprietary processes and advanced testing capabilities, UNIBRAZE is recognized for our quality aluminum welding products.

UNIBRAZE *exceptional products, quality and service for superior welding performance.*



C.W.B. APPROVED



SHAVED - TRIPLE DEGREASED PRECISION LEVEL LAYER WOUND

ALLOY	DIAMETER	
	MM	INCHES
4043 36" LENGTHS 10# TUBES	1.6	1/16
	2.4	3/32
	3.2	1/8
	4.0	5/32
4043 1# & 5# SPOOLS	0.8	.030
	0.9	.035
	1.2	3/64
	1.6	1/16
4043 16# SPOOLS	0.8	.030
	0.9	.035
	1.2	3/64
	1.6	1/16
5356 36" LENGTHS 10# TUBES	1.6	1/16
	2.4	3/32
	3.2	1/8
	4.0	5/32
5356 1# & 5# SPOOLS	0.8	.030
	0.9	.035
	1.2	3/64
	1.6	1/16
5356 16# SPOOLS	0.8	.030
	0.9	.035
	1.2	3/64
	1.6	1/16

PACKAGING: TIG ROD 10 LB CARTON - 1# SPOOLS
20 LB CARTON - 5# SPOOLS / 20LB / CARTON

SEE UNIBRAZE SHEET TAB 2