

# HOLE SAWS

## Bi-Metal Hole Saws



- Cut through steel, tin, aluminum, fiberglass, wood and plastic.
- Deep 1-5/8" (41.3 mm) cutting depth allows for cutting through 2" x 4" wood studs.
- Extra-tough bi-metal blade – we use the highest grade of tool steel to outlast competitor's blades. That beats premature saw replacement and saves you money.
- Steam oxide finish – no paint to gum up and slow cutting. The saw runs cooler for longer life and better performance.
- Extra-thick backplate minimizes vibration for smoother, easier, less tiring cutting.
- Made in USA

| CAT. NO.   | UPC NO. |        |       |        |              |        | USE WITH QUICK CHANGE |                        |       |       |
|------------|---------|--------|-------|--------|--------------|--------|-----------------------|------------------------|-------|-------|
| 825-5/8    | 19132   | 5/8    | 15.9  |        | Pg-9         | 1/4"   | 02800*                | 37157, 37155, or 38522 | .1 46 |       |
| 825-3/4    | 19134   | 3/4    | 19.0  |        | Pg-11        | 1/2"   |                       |                        | .1 46 |       |
| 825-13/16  | 19135   | 13/16  | 20.6  |        | Pg-13 ISO-20 | 1/2"   |                       |                        | .1 46 |       |
| 825-7/8    | 19136   | 7/8    | 22.2  | 1/2"   | Pg-16        | 5/8"   |                       |                        | .1 46 |       |
| 825-1      | 19138   | 1      | 25.4  |        |              | ISO-25 |                       |                        | 3/4"  | .1 46 |
| 825-1-1/8  | 19141   | 1-1/8  | 28.6  | 3/4"   | Pg-21        | 3/4"   |                       |                        | .1 46 |       |
| 825-1-3/16 | 19143   | 1-3/16 | 30.2  |        |              |        |                       |                        | .2 91 |       |
| 825-1-1/4  | 19144   | 1-1/4  | 31.7  |        |              | 1"     |                       |                        | .2 91 |       |
| 825-1-5/16 | 19145   | 1-5/16 | 33.3  |        |              | ISO-32 |                       |                        | .2 91 |       |
| 825-1-3/8  | 19146   | 1-3/8  | 35.0  | 1"     |              |        |                       |                        | .1 46 |       |
| 825-1-7/16 | 19147   | 1-7/16 | 36.5  |        | Pg-29        |        | .2 91                 |                        |       |       |
| 825-1-1/2  | 19148   | 1-1/2  | 38.1  |        |              | 1-1/4" | .2 91                 |                        |       |       |
| 825-1-5/8  | 19150   | 1-5/8  | 41.3  |        |              | ISO-40 | .2 91                 |                        |       |       |
| 825-1-3/4  | 19152   | 1-3/4  | 44.4  | 1-1/4" |              | 1-1/2" | .2 91                 |                        |       |       |
| 825-1-7/8  | 19154   | 1-7/8  | 47.6  |        | Pg-36        |        | .3 137                |                        |       |       |
| 825-2      | 19155   | 2      | 50.8  | 1-1/2" |              | ISO-50 | .2 91                 |                        |       |       |
| 825-2-1/8  | 19158   | 2-1/8  | 54.0  |        | Pg-42        |        | .3 137                |                        |       |       |
| 825-2-1/4  | 19159   | 2-1/4  | 57.2  |        |              | 2"     | .3 137                |                        |       |       |
| 825-2-3/8  | 19161   | 2-3/8  | 60.3  |        | Pg-48        | 2"     | .3 137                |                        |       |       |
| 825-2-1/2  | 19162   | 2-1/2  | 63.5  | 2"     |              | ISO-63 | 2"                    |                        |       |       |
| 825-2-5/8  | 19164   | 2-5/8  | 66.7  |        |              |        | .4 182                |                        |       |       |
| 825-2-3/4  | 19165   | 2-3/4  | 69.8  |        |              |        | .4 182                |                        |       |       |
| 825-2-7/8  | 19166   | 2-7/8  | 73.0  |        |              |        | .4 182                |                        |       |       |
| 825-3      | 19167   | 3      | 76.2  | 2-1/2" |              | 2-1/2" | .5 227                |                        |       |       |
| 825-3-1/8  | 19168   | 3-1/8  | 79.4  |        |              |        | .5 227                |                        |       |       |
| 825-3-1/4  | 19169   | 3-1/4  | 82.5  |        |              |        | .6 273                |                        |       |       |
| 825-3-1/2  | 19171   | 3-1/2  | 88.9  |        |              |        | .6 273                |                        |       |       |
| 825-3-5/8  | 19172   | 3-5/8  | 92.1  | 3"     |              |        | .6 273                |                        |       |       |
| 825-3-3/4  | 19174   | 3-3/4  | 95.2  |        |              |        | .7 318                |                        |       |       |
| 825-4      | 19176   | 4      | 101.6 |        |              |        | .7 318                |                        |       |       |
| 825-4-1/8  | 19177   | 4-1/8  | 104.8 | 3-1/2" |              | 3-1/2" | .8 363                |                        |       |       |
| 825-4-1/4  | 19178   | 4-1/4  | 108.0 |        |              | 4"     | .8 363                |                        |       |       |
| 825-4-3/8  | 19179   | 4-3/8  | 111.1 |        |              |        | .8 363                |                        |       |       |
| 825-4-1/2  | 19180   | 4-1/2  | 114.3 | 4"     |              |        | 9 409                 |                        |       |       |
| 825-4-3/4  | 19181   | 4-3/4  | 120.6 |        |              |        | 1.1 499               |                        |       |       |
| 825-5      | 19182   | 5      | 127.0 |        |              |        | 1.2 545               |                        |       |       |
| 825-5-1/2  | 19183   | 5-1/2  | 139.7 |        |              | 5"     | 1.2 545               |                        |       |       |
| 825-6      | 19184   | 6      | 152.4 |        |              |        | 1.4 636               |                        |       |       |
| 825-68     | 36169   | 68     | 68.0  |        |              |        | .4 182                |                        |       |       |
| 825-74     | 36170   | 74     | 70.0  |        |              |        | .5 227                |                        |       |       |

\*See page 207 for Quick Change adapter information.