Gator-Plus[™] Battery-Powered 4-Ton Crimping Tools





KC4 DIES FOR SERVICE ENTRANCE CONNECTORS						
CAT. NO.	UPC NO.	DESCRIPTION				
KC4-10	02021	Crimping Dies for 5/8" Service Entrance Connectors				
KC4-840	02022	Crimping Dies for 840 Service Entrance Connectors				

- New breakthrough hydraulic pump design results in an extremely compact battery-powered crimping tool with capacity to 250 kcmil (MCM) copper color-coded connectors. Also crimps 5/8 and 840 service entrance connectors.
 Special compact 9.6 volt Ni-Cd battery reduces weight and size.
- Slim profile and light weight provide for one-hand operation.
- Can complete approximately 85 crimps per battery charge with 4/0 copper connectors.
- Ram automatically retracts to signal that crimp is complete.
- Ram can be retracted in mid-cycle to adjust connector.
- Flip-open crimping head rotates 360°.
- UL and cUL Classified with Anderson, Blackburn, Burndy, ILSCO, Panduit, Penn-Union, and Thomas & Betts **copper** color-coded code connectors.
- Includes two batteries, battery charger, and molded carrying case.
- Choice of 120 volt, 230 volt, or 12 volt battery charger.

CAT. NO.	UPC NO.	DESCRIPTION
EK41011	02033	4-Ton Battery-Powered Crimping Tool, 120 V Charger
EK41012	02034	4-Ton Battery-Powered Crimping Tool, 12 V Charger
EK41022	02035	4-Ton Battery-Powered Crimping Tool, 230 V Charger

Crimping Dies shown below.

SPECIFICATIONS				
Capacity	#8 AWG to 250 kcmil (MCM) copper color-coded connectors 5/8 service entrance connectors 840 service entrance connectors			
Crimping Force	7,900 lb. (35 kN)			
Length	14" (356 mm) 3-1/8" (79 mm)			
Width				
Weight	3.6 lbs. (1.6 kg)			
Crimp Cycle Time	~4 seconds			
Battery	9.6 volt 1.3 Ah Ni-Cd battery			
Battery Charge Time	1 Hour			

4-TON CRIMPING DIE KIT*								
CAT. NO.	UPC NO.	DESCRIPTI	ON					
KC4CU	02037	Complete Die Set for copper connector. Includes dies for #8 to 250 kcmil (MCM) copper connectors (dies can be stored in tool carrying case).						
DIES FOR CRIMPING COLOR-CODED COPPER LUGS & SPLICES*								
CAT. NO.	U	IPC NO.	COPPER CABLE SIZE	COLOR CODE				
KC4-8	0	2075	8 AWG	Red				
KC4-6	0	2076	6 AWG	Blue				
KC4-4	0	2077	4 AWG	Gray				
KC4-2	0	2078	2 AWG	Brown				

1 AWG

1/0 AWG

2/0 AWG

3/0 AWG

4/0 AWG

250 kcmil (MCM)

*Note: Connections are UL and cUL classified for copper when used with Anderson, Blackburn, FCI Burndy, ILSCO, Panduit, Thomas & Betts and Penn-Union color-coded lugs and splices.

KC4-1

KC4-1/0

KC4-2/0

KC4-3/0

KC4-4/0

KC4-250

02079

02080

02081

02082

02083

02084

Green

Pink

Black

Orange

Purple

Yellow