

HOSE STEMS

G23S Stems feature long shanks for extra fitting retention, and collars for use with G29C interlocking clamps. Sizes up to and including 1" are carbon steel. Sizes above 1" are made from ductile iron. All G23S series stems are zinc plated.

G29C BOLT CLAMPS

G29C clamps are designed to lock into the collars provided on G23S and G29S hose stems. This feature prevents fitting pull-out. G29C clamps are plated ductile iron. Clamps have two, four, or even six bolts depending on size.

3

Air & Mining

Part Number	Pipe Size	Hose Size	PRICE EACH		Pkg Qty
			Loose	Std Pkg	

G23S... STEEL MALE NPT HOSE BARB



G23S-013-025	1/8"	1/4"	\$ 3.90	\$ 3.50	5
G23S-025-025	1/4"	1/4"	3.90	3.50	5
G23S-025-038	1/4"	3/8"	3.40	3.10	5
G23S-025-050	1/4"	1/2"	5.00	4.60	5
G23S-038-025	3/8"	1/4"	5.00	4.50	5
G23S-038-038	3/8"	3/8"	3.70	3.30	5
G23S-038-050	3/8"	1/2"	4.90	4.50	5
G23S-050-038	1/2"	3/8"	4.60	4.20	5
G23S-050-050	1/2"	1/2"	5.00	4.60	5
G23S-050-075	1/2"	3/4"	9.00	8.00	5
G23S-075-050	3/4"	1/2"	9.00	8.00	5
G23S-075-075	3/4"	3/4"	7.90	7.10	5
G23S-075-100	3/4"	1"	9.60	8.60	5
G23S-100-075	1"	3/4"	13.50	12.20	5
G23S-100-100	1"	1"	11.30	10.10	5
G23S-125-125	1 1/4"	1 1/4"	12.50	11.10	5
G23S-150-150	1 1/2"	1 1/2"	15.70	14.10	5
G23S-200-200	2"	2"	22.30	20.10	5
G23S-250-250	2 1/2"	2 1/2"		45.50	1
G23S-300-300	3"	3"		56.20	1
G23S-400-400	4"	4"		102.80	1

Hoses can whip if they become accidentally uncoupled or tear away from the fitting. G29R safety cables act to control whipping in the event of a failure. To function properly, restraint cables must be installed in a fully extended position with no slack.

Part No.	Description	PRICE EACH
----------	-------------	------------

G29R... HOSE RESTRAINT CABLES



G29R-125	1/8" Cable for 1/2" to 1 1/4" Hose	\$ 12.50
G29R-300	1/4" Cable for 1 1/2" to 3" Hose	20.50

Part Number	Nom. Size	Hose Min	O.D. Max	Cross Ref	Tighten Torque*	PRICE EACH		Pkg Qty
						Loose	StdPkg	

G29C... BOLT CLAMPS



G29C-038	3/8"	0.69"	0.88"	CD	6	\$ 5.10	\$ 4.70	5
G29C-050AA	1/2"	0.81"	0.94"	DD	6	5.40	5.00	5
G29C-050A	1/2"	0.94"	1.06"	B4	12	5.40	5.00	5
G29C-050B	1/2"	1.06"	1.19"	B5	12	5.90	5.30	5
G29C-075AA	3/4"	1.16"	1.28"	BU9S	21	6.60	6.00	5
G29C-075A	3/4"	1.19"	1.31"	BU9	21	6.60	6.00	5
G29C-075B	3/4"	1.31"	1.50"	B9	21	7.70	6.90	5
G29C-075C	3/4"	1.50"	1.69"	B10	21	9.10	8.10	5
G29C-100AA	1"	1.41"	1.56"	156	21	11.60	10.50	5
G29C-100A	1"	1.53"	1.72"	BU14	21	11.60	10.50	5
G29C-100B	1"	1.63"	1.84"	B14	21	11.60	10.50	5
G29C-100C	1"	1.88"	2.06"	B15	21	15.50	13.90	5
G29C-125	1 1/4"	2.06"	2.25"	B19	40	17.60	15.70	5
G29C-150AAA	1 1/2"	1.81"	2.00"	BU22	40	19.20	17.30	5
G29C-150AA	1 1/2"	2.00"	2.22"	B22	40	19.20	17.30	5
G29C-150A	1 1/2"	2.09"	2.28"	BU24	40	20.60	18.50	5
G29C-150B	1 1/2"	2.25"	2.44"	B24	40	20.60	18.50	5
G29C-150C	1 1/2"	2.47"	2.72"	B25	60	24.20	21.80	5
G29C-200AA	2"	2.34"	2.53"	BU28	60	25.10	22.50	5
G29C-200A	2"	2.50"	2.78"	BU29	60	25.10	22.50	5
G29C-200B	2"	2.75"	3.06"	B29	60	29.20	26.20	5
G29C-200C	2"	3.09"	3.44"	B30	150	50.90	45.80	5
G29C-250	2 1/2"	3.50"	3.94"	B34	150		51.40	1
G29C-300AA	3"	3.50"	3.94"	BU35	150		50.90	1
G29C-300A	3"	3.81"	4.19"	B35	200		53.00	1
G29C-400AA	4"	4.25"	4.81"	BS39	200		168.50	1

* Recommended tightening torque for dry (un-lubricated) bolts in ft. lbs.

G29R... Hose Restraint Cable

