


Pipe Fittings



MALLEABLE IRON FITTING (CLASS 150 STANDARD)

Couplings
Figure 1125

Size (NPS)	M (in)	Weight (lbs)	
		black	galv.
1/4	1/8	1	.07 .08
3/8	1/8	1-1/8	.11 .13
	1/4		.11 .12
1/2	1/8	1-1/4	.14 .15
	3/8		.15 .16
3/4	1/8	1-7/16	.24 .25
	1/4		.22 .23
	3/8		.25 .26
	1/2		.26 .28
1	1/4	1-11/16	.35 .37
	3/8		.35 .38
	1/2		.39 .41
	3/4		.42 .44
1-1/4	1/2	2-1/16	.60 .63
	3/4		.64 .65
1-1/2	1		.68 .70
	1/2	2-5/16	.77 .80
	3/4		.88 .90
	1		.90 .91
2	1/2	2-13/16	1.15 1.20
	3/4		1.34 1.34
	1		1.40 1.40
	1-1/4		1.53 1.53
	1-1/2		1.55 1.57
2-1/2	1	3-1/4	2.12 2.20
	1-1/4		2.09 2.14
	1-1/2		2.09 2.11
	2		2.50 2.56
3	1	3-11/16	3.16 3.24
	1-1/4		3.22 3.05
	1-1/2		3.30 3.47
	2		3.23 3.38
	2-1/2		3.31 3.40
3-1/2	2	4	4.32 4.40
	2-1/2		4.72 4.80
	3		4.99 5.15
4	1-1/2	4-3/8	4.90 5.00
	2		5.10 5.00
	2-1/2		5.93 5.95
	3		6.55 6.62
5	3-1/2		6.30 6.45
	4	4-9/16	9.57 9.20
6	4	4-13/16	10.30 10.70



Return Bends
Open Pattern,
R.H. Fig: 1119



Size (NPS)	Center to Center (in)	Weight (lbs)	
		black	galv.
1/2	1-1/2	.36	—
3/4	2	.64	—
1	2-1/2	1.10	1.15
1-1/4	3	1.77	—
1-1/2	3-1/2	2.55	—
2	4	4.00	4.25


Cap
Figure 1124



Size (NPS)	Weight (lbs)	
	black	galv.
•1/8	.03	.04
•1/4	.06	.06
•3/8	.09	.10
1/2	.12	.12
3/4	.22	.20
1	.38	.38
1-1/4	.58	.61
1-1/2	.73	.75
2	1.13	1.20
2-1/2	1.75	1.80
3	2.59	2.75
3-1/2	3.16	3.24
4	4.54	4.61
5	6.44	6.89
6	10.00	9.98

•1/8, 1/4, 3/8 Made in Steel

Hex Locknut
Figure 1134



Size (NPS)	Minimum Dimensions				Weight (lbs)	
	A (in)	B (in)	C (in)	D (in)	black	galv.
•1/8	.690	.500	.190	.040	.04	.04
•1/4	.840	.660	.250	.060	.02	.03
3/8	1.000	.770	.280	.060	.04	.04
1/2	1.180	.970	.310	.060	.06	.06
3/4	1.430	1.230	.340	.060	.12	.13
1	1.750	1.500	.380	.060	.14	.16
1-1/4	2.100	1.860	.420	.060	.21	.19
1-1/2	2.350	2.120	.470	.060	.24	.25
2	2.880	2.630	.530	.090	.40	.47

•1/8 & 1/4 Made in Steel