

- S = SOCKET, SPG = SPIGOT, MPT = MALE PIPE THREAD, FPT = FEMALE PIPE THREAD
- ALL DIMENSIONS ARE IN INCHES.


TOLERANCES

- S = (SOCKET LENGTH) MINIMUM
 - G = (LAYING LENGTH) INTERSECTION OF CENTER LINES TO BOTTOM OF SOCKET/THREAD, 90° ELBOWS, TEES, CROSSES, $\pm 1/32''$
 - H = INTERSECTION OF CENTER LINES TO FACE OF FITTINGS; 90° ELBOWS, TEES, CROSSES, $\pm 1/32''$
 - J = (LAYING LENGTH) INTERSECTION OF CENTER LINES TO BOTTOM OF SOCKET/THREAD; 45° ELBOWS, $\pm 1/32''$
 - L = OVERALL LENGTH OF FITTINGS, (INCLUDING CAPS), $\pm 1/16''$
 - M = OUTSIDE DIAMETER OF SOCKET/THREAD HUB, $\pm 1/16''$
 - N = SOCKET/THREAD BOTTOM TO SOCKET/THREAD BOTTOM; COUPLINGS, $\pm 1/16''$
- DIMENSIONS ARE SUBJECT TO CHANGE WITHOUT NOTIFICATION.

Tee

S x S x S

PVC PART NO. 8400



Size	L	H	G	Approx Wt. (Lbs.)
1/2	2 ¹⁵ / ₁₆	1 ¹⁵ / ₃₂	1 ⁹ / ₃₂	0.11
3/4	3 ⁷ / ₁₆	1 ²³ / ₃₂	1 ¹ / ₁₆	0.17
1	4	2	2 ⁷ / ₃₂	0.29
1 1/4	4 ⁹ / ₁₆	2 ⁹ / ₃₂	1	0.42
1 1/2	4 ⁷ / ₈	2 ⁷ / ₁₆	1 ¹ / ₃₂	0.51
2	5 ³ / ₄	2 ⁷ / ₈	1 ⁵ / ₁₆	0.84
2 1/2	6 ¹⁵ / ₁₆	3 ¹⁵ / ₃₂	1 ²¹ / ₃₂	1.49
3	7 ¹ / ₂	3 ³ / ₄	1 ²⁷ / ₃₂	2.38
4	9 ³ / ₈	4 ¹¹ / ₁₆	2 ⁷ / ₁₆	3.76
6	14 ¹ / ₈	7 ¹ / ₁₆	4 ¹ / ₃₂	10.75
8	17 ¹⁹ / ₃₂	8 ¹³ / ₁₆	4 ³ / ₄	20.13