1/4" DRIVE DEEP SOCKETS - 6 POINT

- Proto® 6 Point Sockets are ideal for use on stubborn or damaged fasteners, and also on fasteners made from soft materials.
- TorquePlus™ features apply.

TORQUEPLUS FASTENING SYSTEM

Product #	Size (in) (A)	Nut End Outside Dia. (in) (B)	Drive End Outside Dia. (in) (C)	Nut Depth (in) (D)	Bolt Clearance Depth (in) (E)	Overall Length (in) (L)	Weight (lbs)
J4706L	3/16	5/16	15/32	9/32	1-21/32	2	0.05
J4707L	7/32	11/32	15/32	3/8	1-21/32	2	0.05
J4708L	1/4	25/64	15/32	3/8	1-1/2	2	0.05
J4709L	9/32	7/16	15/32	3/8	1-1/2	2	0.05
J4710L	5/16	15/32	15/32	3/8	1-1/2	2	0.06
J4711L	11/32	1/2	1/2	5/8	1-1/2	2	0.06
J4712L	3/8	9/16	9/16	5/8	1-27/64	2	0.08
J4714L	7/16	37/64	39/64	5/8	1-27/64	2	0.09
J4716L	1/2	11/16	11/16	5/8	1-27/64	2	0.13
J4718L	9/16	3/4	3/4	5/8	1-27/64	2	0.14

ASME B107.1

1/4" DRIVE METRIC DEEP SOCKETS - 6 POINT

METRIC

- Proto® 6 Point Sockets are ideal for use on stubborn or damaged fasteners, and also on fasteners made from soft materials.
- TorquePlus™ features apply.

TORQUEPLUS FASTENING SYSTEM

Product #	Size (mm) (A)	Nut End Outside Dia. (in) (B)	Drive End Outside Dia. (in) (C)	Nut Depth (in) (D)	Bolt Clearance Depth (in) (E)	Overall Length (in) (L)	Weight (lbs)
J4704LM	4	9/32	29/64	13/64	55/64	1-63/64	0.04
J4705LM	5	5/16	29/64	9/32	55/64	1-63/64	0.04
J47055LM	5.5	11/32	29/64	9/32	55/64	1-63/64	0.04
J4706LM	6	3/8	29/64	3/8	55/64	1-63/64	0.04
J4707LM	7	27/64	29/64	3/8	55/64	1-63/64	0.04
J4708LM	8	29/64	29/64	13/32	1-5/32	1-63/64	0.06
J4709LM	9	1/2	1/2	39/64	1-5/32	1-63/64	0.06
J4710LM	10	9/16	9/16	5/8	1-27/64	1-63/64	0.07
J4711LM	11	39/64	39/64	5/8	1-27/64	1-63/64	0.09
J4712LM	12	21/32	21/32	5/8	1-27/64	1-63/64	0.11
J4713LM	13	11/16	11/16	5/8	1-27/64	1-63/64	0.15
J4714LM	14	49/64	49/64	5/8	1-27/64	1-63/64	0.15
J4715LM	15	53/64	53/64	5/8	1-27/64	2	0.20

ASME B107.5M