



3/8" DRIVE DEEP SOCKETS - 12 POINT

- ▶ Proto® 12 Point Sockets are ideal for use on stubborn or damaged fasteners, and also on fasteners made from soft materials.
- ▶ TorquePlus™ features apply.




Product #	Size (in) (A)	Nut End Outside Dia. (in) (B)	Drive End Outside Dia. (in) (C)	Nut Depth (in) (D)	Bolt Clearance Depth (in) (E)	Overall Length (in) (L)	Weight (lbs)
J5008	1/4	13/32	21/32	5/16	1-11/16	2-1/8	0.10
J5010	5/16	15/32	21/32	13/32	1-11/16	2-1/8	0.10
J5011	11/32	1/2	21/32	25/64	1-11/16	2-1/8	0.09
J5012	1/4	35/64	21/32	13/32	1-11/16	2-1/8	0.10
J5014	3/32	21/32	21/32	7/16	1-11/16	2-1/8	0.12
J5016	1/2	23/32	23/32	33/64	1-11/16	2-1/8	0.14
J5018	9/16	51/64	51/64	19/32	1-11/16	2-1/8	0.18
J5020	5/8	7/8	7/8	43/64	2-5/16	2-3/4	0.24
J5022	11/16	15/16	15/16	43/64	2-5/16	2-3/4	0.30
J5024	3/4	1-1/64	1-1/64	43/64	2-5/16	2-3/4	0.33
J5026	13/16	1-5/64	1-5/64	43/64	2-5/16	2-3/4	0.36
J5028	7/8	1-15/64	1-15/64	1-3/16	2-5/16	2-3/4	0.43
J5030	15/16	1-15/64	1-15/64	1-3/16	2-5/16	2-3/4	0.46
J5032	1	1-5/16	1-5/16	1-3/16	2-5/16	2-3/4	0.54



AS954E S3.8.1

ASME B107.1



3/8" DRIVE METRIC DEEP SOCKETS - 12 POINT

METRIC

- ▶ Proto® 12 Point Sockets are ideal for use on stubborn or damaged fasteners, and also on fasteners made from soft materials.
- ▶ TorquePlus™ features apply.



Product #	Size (mm) (A)	Nut End Outside Dia. (in) (B)	Drive End Outside Dia. (in) (C)	Nut Depth (in) (D)	Bolt Clearance Depth (in) (E)	Overall Length (in) (L)	Weight (lbs)
J5006M	6	25/64	21/32	5/16	1-13/16	2-1/8	0.11
J5007M	7	25/64	21/32	25/64	1-47/64	2-1/8	0.09
J5008M	8	15/32	21/32	25/64	1-47/64	2-1/8	0.10
J5009M	9	33/64	21/32	25/64	1-47/64	2-1/8	0.11
J5010M	10	37/64	21/32	25/64	1-47/64	2-1/8	0.12
J5011M	11	21/32	7/16	1-11/16	1-47/64	2-1/8	0.13
J5012M	12	45/64	45/64	33/64	1-39/64	2-1/8	0.13
J5013M	13	23/32	23/32	33/64	1-39/64	2-1/8	0.13
J5014M	14	25/32	25/32	19/32	1-17/32	2-1/8	0.15
J5015M	15	55/64	55/64	21/32	2-7/64	2-3/4	0.15
J5016M	16	55/64	55/64	21/32	2-7/64	2-3/4	0.24
J5017M	17	15/16	15/16	21/32	2-7/64	2-3/4	0.27
J5018M	18	15/16	15/16	21/32	2-7/64	2-3/4	0.28
J5019M	19	1-1/64	1-1/64	11/16	2-1/16	2-3/4	0.30
J5020M	20	1-5/64	1-5/64	11/16	2-1/16	2-3/4	0.33
J5021M	21	1-5/64	1-5/64	11/16	2-1/16	2-3/4	0.34
J5022M	22	1-11/64	1-11/64	11/16	2-1/16	2-3/4	0.45
J5023M	23	1-7/32	1-11/64	1-3/16	1-37/64	2-3/4	0.54
J5026M	26	1-5/64	1-5/64	43/64	2-5/16	2-3/4	0.28



AS954E S3.8.1

ASME B107.5M