3/8" DRIVE DEEP SOCKETS - 6 POINT

- Proto® 6 Point Sockets are ideal for use on stubborn or damaged fasteners, and also on fasteners made from soft materials.
- TorquePlus™ features apply.

TORQUEPLUS FASTENING SYSTEM

Product #	Size (in) (A)	Nut End Outside Dia. (in) (B)	Drive End Outside Dia. (in) (C)	Nut Depth (in) (D)	Bolt Clearance Depth (in) (E)	Overall Length (in) (L)	Weight (lbs)
J5008H	1/4	25/64	41/64	21/64	1-11/16	2-1/8	0.12
J5010H	5/16	11/32	41/64	11/32	1-11/16	2-1/8	0.10
J5011H	11/32	1/2	41/64	21/32	1-11/16	2-1/8	0.10
J5012H	3/8	9/16	41/64	11/32	1-11/16	2-1/8	0.11
J5014H	7/16	41/64	41/64	7/16	1-11/16	2-1/8	0.12
J5016H	1/2	23/32	23/32	33/64	1-11/16	2-1/8	0.14
J5018H	9/16	51/64	51/64	19/32	1-11/16	2-1/8	0.17
J5020H	5/8	7/8	7/8	21/32	1-11/16	2-3/4	0.25
J5022H	11/16	61/64	61/64	21/32	1-23/32	2-3/4	0.29
J5024H	3/4	1-1/64	1-1/64	11/16	1-23/32	2-3/4	0.32
J5026H	13/16	1-5/64	1-5/64	11/16	2-5/64	2-3/4	0.35
J5028H	7/8	1-11/64	1-11/64	11/16	2-5/64	2-3/4	0.40
J5030H	15/16	1-15/64	1-15/64	1-3/16	2-5/64	2-3/4	0.52
J5032H	1	1-21/64	1-21/64	1-3/16	2-5/64	2-3/4	0.58

ASME B107.1



3/8" DRIVE METRIC DEEP SOCKETS - 6 POINT

METRIC

- Proto® 6 Point Sockets are ideal for use on stubborn or damaged fasteners, and also on fasteners made from soft materials.
- TorquePlus™ features apply.

TORQUEPLUS FASTENING SYSTEM

Product #	Size (mm) (A)	Nut End Outside Dia. (in) (B)	Drive End Outside Dia. (in) (C)	Nut Depth (in) (D)	Bolt Clearance Depth (in) (E)	Overall Length (in) (L)	Weight (lbs)
J5006MH	6	25/64	21/32	5/16	1-11/16	2-1/8	0.10
J5007MH	7	27/64	21/32	5/16	1-11/16	2-1/8	0.09
J5008MH	8	15/32	21/32	5/16	1-15/16	2-1/8	0.10
J5009MH	9	33/64	21/32	25/64	1-11/16	2-1/8	0.10
J5010MH	10	37/64	21/32	25/64	1-11/16	2-1/8	0.11
J5011MH	11	21/32	21/32	7/16	1-11/16	2-1/8	0.12
J5012MH	12	45/64	45/64	33/64	1-1/2	2-1/8	0.14
J5013MH	13	23/32	23/32	33/64	1-1/2	2-1/8	0.15
J5014MH	14	25/32	25/32	19/32	1-1/2	2-1/8	0.16
J5015MH	15	55/64	55/64	21/32	2-5/16	2-3/4	0.24
J5016MH	16	55/64	55/64	21/32	2-5/16	2-3/4	0.24
J5017MH	17	15/16	15/16	21/32	2-5/16	2-3/4	0.28
J5018MH	18	15/16	15/16	21/32	2-5/16	2-3/4	0.28
J5019MH	19	1-1/64	1-1/64	11/16	2-5/16	2-3/4	0.33
J5020MH	20	1-5/64	1-5/64	11/16	2-5/16	2-3/4	0.35
J5021MH	21	1-5/64	1-5/64	11/16	2-5/16	2-3/4	0.35
J5022MH	22	1-11/64	1-11/64	11/16	2-5/16	2-3/4	0.46
J5023MH	23	1-15/64	1-15/64	1-3/16	2-5/16	2-3/4	0.55
J5024MH	24	1-9/32	1-9/32	1-3/16	2-5/16	2-3/4	0.56
J5025MH	25	1-9/32	1-9/32	1-3/16	2-5/16	2-3/4	0.56
J5026MH	26	1-9/32	1-9/32	1-3/16	2-5/16	2-3/4	0.65

ASME B107.5M