

1/2" DRIVE METRIC SOCKETS - 12 POINT



- ▶ Proto® 12 Point Sockets are ideal for use on stubborn or damaged fasteners, and also on fasteners made from soft materials.
- ▶ TorquePlus™ features apply.



| Product # | Size (mm) (A) | Nut End Outside Dia. (in) (B) | Drive End Outside Dia. (in) (C) | Nut Depth (in) (D) | Bolt Clearance Depth (in) (E) | Overall Length (in) (L) | Weight (lbs) |
|-----------|------------------|----------------------------------|------------------------------------|-----------------------|----------------------------------|----------------------------|--------------|
| J5408M | 8 | 35/64 | 55/64 | 23/64 | 25/32 | 1-19/64 | 0.11 |
| J5409M | 9 | 19/32 | 55/64 | 23/64 | 25/32 | 1-31/64 | 0.11 |
| J5410M | 10 | 39/64 | 55/64 | 23/64 | 55/64 | 1-31/64 | 0.11 |
| J5411M | 11 | 45/64 | 55/64 | 23/64 | 55/64 | 1-31/64 | 0.11 |
| J5412M | 12 | 47/64 | 55/64 | 23/64 | 55/64 | 1-31/64 | 0.11 |
| J5413M | 13 | 3/4 | 55/64 | 23/64 | 55/64 | 1-31/64 | 0.12 |
| J5414M | 14 | 13/16 | 55/64 | 23/64 | 7/8 | 1-1/2 | 0.13 |
| J5415M | 15 | 55/64 | 55/64 | 37/64 | 7/8 | 1-1/2 | 0.13 |
| J5416M | 16 | 7/8 | 7/8 | 37/64 | 7/8 | 1-1/2 | 0.13 |
| J5417M | 17 | 61/64 | 61/64 | 37/64 | 7/8 | 1-1/2 | 0.14 |
| J5418M | 18 | 61/64 | 61/64 | 37/64 | 7/8 | 1-1/2 | 0.17 |
| J5419M | 19 | 1-1/32 | 1-1/32 | 11/16 | 27/32 | 1-1/2 | 0.19 |
| J5420M | 20 | 1-3/32 | 1-3/32 | 11/16 | 27/32 | 1-1/2 | 0.22 |
| J5421M | 21 | 1-3/32 | 1-3/32 | 11/16 | 27/32 | 1-1/2 | 0.24 |
| J5422M | 22 | 1-11/64 | 1-11/64 | 11/16 | 27/32 | 1-17/32 | 0.26 |
| J5423M | 23 | 1-13/64 | 1-13/64 | 25/32 | 59/64 | 1-17/32 | 0.27 |
| J5424M | 24 | 1-1/4 | 1-1/4 | 53/64 | 59/64 | 1-17/32 | 0.28 |
| J5425M | 25 | 1-9/32 | 1-9/32 | 53/64 | 59/64 | 1-17/32 | 0.30 |
| J5426M | 26 | 1-21/64 | 1-21/64 | 55/64 | 63/64 | 1-39/64 | 0.33 |
| J5427M | 27 | 1-13/32 | 1-13/32 | 15/16 | 1-3/64 | 1-43/64 | 0.39 |
| J5428M | 28 | 1-31/64 | 1-31/64 | 63/64 | 1-5/32 | 1-25/32 | 0.48 |
| J5429M | 29 | 1-31/64 | 1-31/64 | 63/64 | 1-5/32 | 1-25/32 | 0.62 |
| J5430M | 30 | 1-9/16 | 1-17/32 | 63/64 | 1-5/32 | 1-25/32 | 0.63 |
| J5431M | 31 | 1-39/64 | 1-39/64 | 1-1/16 | 1-5/32 | 1-25/32 | 0.63 |
| J5432M | 32 | 1-39/64 | 1-39/64 | 1-1/8 | 1-7/32 | 1-27/32 | 0.63 |
| J5434M | 34 | 1-49/64 | 1-49/64 | 1 | 1-35/64 | 1-27/32 | 0.63 |
| J5436M | 36 | 1-31/32 | 1-31/32 | 1-3/8 | 1-39/64 | 2-15/64 | 1.04 |
| J5438M | 38 | 2-1/32 | 2-1/32 | 1-3/8 | 1-39/64 | 2-1/4 | 1.04 |



AS954E S3.8.1

ASME B107.5M

