LED-8030M High Bay / Area

 SKU (USA)
 SKU (Canada)
 Description


 LED-8030M30
 LED-8030M30C
 150W 3000K

 LED-8030M42
 LED-8030M42C
 150W 4200K


 LED-8030M57
 LED-8030M57C
 150W 5700K



LLD 00301137			
Technical Specifications			
Models US/CAN	LED-8030M30/ LED-8030M30C	LED-8030M42/ LED-8030M42C	LED-8030M57/ LED-8030M57C
ССТ	3000K	4200K	5700K
Power Consumption	150 watts		
Replaces	400w MH/HPS		
Mounting	E39		
Voltage	120-277VAC (USA) 120-347VAC (CANADA)		
LED Type	398 Samsung #5630 SMD		
Beam Angle	360		
Dimmable	No		
Operating Temp	-40°F - +122°F		
Rated R70 Life	Up to 50,000 Hrs.		
Warranty	5 Year Limited*		
LM79			
Specifications	No	Yes	Yes
Power (W)	150	151.8	154.4
ССТ	3000	4287	5574
Lumen Output	>12000	15515	14921
Efficacy	>80	102.2	96.6
THD @ 120V	n/a	n/a	n/a
THD @ 277V	n/a	20.00%	19.27%
PF @ 120V	n/a	n/a	n/a
PF @ 277V	n/a	0.961	0.965
CRI:	>80	84.1	85.8
R9	n/a	16	34
Duv	n/a	0.0002	-0.0027
	2 / Master Carton		
Packaging	2/1	viaster Cai	Iton
Packaging Unit		6" x 12.1	
	11.6" x 11		' 5.24 lbs.



NOTE: Light Efficient Design is providing this information to the general public. Please note that all products contained herein are trademarked, copyrighted, and/or have patents pending. Any use of these designs is strictly prohibited without prior written consent. Light Efficient Design protects its proprietary information vigorously in the courts of the United States of America.





Description:

150W LED retrofit lamp to replace MH and HPS lamps up to 400w, E39 Mogul base. UL listed approved for damp environments & <u>fully enclosed</u> fixtures. Retrofitted fixture retains UL approval under UL Classified 1598C.

Features:

- Replaces 400w HID Lamps
- 120-277V or 120-347V (Canada)
- UL approved for fully enclosed fixtures and damp environments (USA & Can)
- Active Cooling Fan >70,000 hr. rated life
- 50,000 rated life
- 5 year limited warranty (see website for details)

Applications:





High Bay

Canopy

Installation Notes:

- When installing LED-8000 series retrofit lamps within HID fixtures, ballast must be bypassed when present.
- 8000 series retrofits are UL damp rated, sealing the fixtures after installation will deliver best results.
- Installing surge/lightning protectors is highly recommended and helps to eliminate premature driver failure caused by surges and other power fluctuations.

