

## Component mounting

### NS 35 DIN rails, tall design, perforated



- The design of the DIN rails complies with European standard EN 60715
- Particular attention has been paid to a high degree of dimensional accuracy and surface tempering
- All DIN rails are also available cut to length

The DIN rails are available with various surface coatings and are suitable for the following applications:

- Zinc plated, for indoor applications
- White passivated, for indoor applications
- Zinc plated and thick layer passivated, for indoor and protected outdoor applications
- Aluminum and copper. As a result of their improved conductivity, these versions can also be used as PEN busbars

Notes:
For dimensional drawings and ordering examples, see page 519.
For PPS ... DIN rail profile cutters, see page 370.
<sup>1)</sup> Please specify the desired length in millimeters when placing your order. See order example.



Perforated, zinc plated, and thick layer passivated

General data
Material / coating

Technical data
Steel / galvanized, passivated with a thick layer

Description	Color
<b>DIN rail, perforated</b> , in acc. with EN 60715 - 35 x 15 mm, galvanized and passivated with a thick layer, tall design, supply length: 2 m	silver
<b>DIN rail, perforated</b> , according to EN 60715 - 35 x 15 mm, galvanized and thick layer passivated, tall design, supply length: 1 m	silver
<b>DIN rail, perforated</b> , in accordance with EN 60715 - 35 x 15 mm, galvanized and thick layer passivated, tall design, for cabinet width / depth of 0.8 m	silver
Length: 755 mm	silver
For cabinet width / depth of 1.0 m, supply length: 955 mm	silver
For cabinet width / depth of 1.2 m, supply length: 1155 mm	silver
<b>DIN rail, perforated</b> in accordance with EN 60715 - 35 x 15 mm, galvanized and thick layer passivated, tall design, supply length: 2 m, cut to length according to the customer specifications <sup>1)</sup>	silver
<b>DIN rail, perforated</b> , according to EN 60715 - 35 x 15 mm, white passivated, tall design, supply length: 2 m	white
<b>DIN rail, perforated</b> similar to EN 60715 - 35 x 15 mm, 1.5 mm thick, tin-plated, tall design, supply length: 2 m	silver

Ordering data		
Type	Order No.	Pcs. / Pkt.
NS 35/15 PERF 2000MM	1201730	5
NS 35/15 PERF 1000MM	1207658	20
NS 35/15 PERF 755MM	1207679	10
NS 35/15 PERF 955MM	1207682	10
NS 35/15 PERF 1155MM	1207695	10
NS 35/15 PERF/...	1208160	1