

Installation and mounting material


Cable glands

Pressure compensation elements

new

For avoiding condensation

- Material: polyamide, stainless steel
- Membrane: acrylic copolymer
- O-ring: NBR
- Ambient temperature: -40°C ... +105°C
- Degree of protection: IP66/IP67/IP69K




Pressure compensation elements

Thread type	Color	Clamping area [mm]	Dimensions [mm]						
			a	b	c	d	e	f	g
M12	light gray	-	17.00	-	10.00	12.00	17.50	18.50	-
M12	black	-	17.00	-	10.00	12.00	17.50	18.50	-
M12	silver	-	17.00	-	10.00	12.00	21.00	18.50	-

Ordering data		
Type	Order No.	Pcs. / Pkt.
A-INB-M12-69KN-P-LG	1415222	5
A-INB-M12-69KN-P-BK	1415223	5
A-INB-M12-69KN-S-S	1415224	5

Metal NPT adapter, metric external thread, NPT internal thread

- Material: brass, nickel-plated
- O-ring: NBR
- Ambient temperature: -20°C ... +80°C



NPT adapter

ERIC
7500651.22.01.00246

Thread type	Color	Clamping area [mm]	Dimensions [mm]						
			a	b	c	d	e	f	g
M20 / 1/2-inch NPT	silver	-	-	-	6.50	20.00	25.00	24.00	-
M25 / 3/4 inch NPT	silver	-	-	-	7.00	25.00	28.00	30.00	-
M32 / 1/1 inch NPT	silver	-	-	-	8.00	32.00	33.00	38.00	-
M40 / 1 1/4 in. NPT	silver	-	-	-	8.00	40.00	26.00	46.00	-

Ordering data		
Type	Order No.	Pcs. / Pkt.
HC-NPT-1/2-M20	1686847	25
HC-NPT-3/4-M25	1686850	25
HC-NPT-1/1-M32	1686863	10
HC-NPT-1 1/4-M40	1687587	10