



Terminal blocks - CLIPLINE complete

1.5 mm² ST... spring-cage connection terminal blocks

Feed-through, multi-conductor, and multi-level terminal blocks and ground terminals

Notes:
1) For additional accessories and technical data, see page 166.
ISH... insulating sleeves and PS ... and PAI ... test accessories cannot be used with the ST 1,5/S-QUATTRO.
For information on installation and using accessories for Ex applications, see page 602.



17.5 A, feed-through terminal block, 4 connections

17.5 A, double-level terminal block



Ex: IECEx
KEMA 01ATEX2129 U / IECEx KEM 06.0043U

Dimensions	Technical data ¹⁾			
	Width	Length	Height	
[mm]	3.5	72	32 (NS 35/7,5)	
Max. electrical data	<i>I</i>_{max.} [A]	<i>U</i>_{max.} [V]	max. Ø [mm²]	AWG (UL)
	17.5	500	0.08 - 1.5	28-16
Max. bridge current	[A]	17.5		
Rated data		IEC	UL / CUL	CSA
Rated voltage	[V]	500	600	600
Nominal current / cross section	[A] / [mm ²]	17.5 / 1.5	10 / -	10 / -
Connection capacity		solid	stranded	Ferrule without/with plastic sleeve
1 conductor	[mm ²]	0.08 - 1.5	0.08 - 1.5	0.14 - 1.5
2 stranded conductors with a TWIN ferrule	[mm ²]	-	-	0.14 - 1
General data				
Stripping length	[mm]	8		

Dimensions	Technical data ¹⁾			
	Width	Length	Height	
[mm]	4.2	67.5	47.5 (NS 35/7,5)	
Max. electrical data	<i>I</i>_{max.} [A]	<i>U</i>_{max.} [V]	max. Ø [mm²]	AWG (UL)
	17.5	500	0.08 - 1.5	26-14
Max. bridge current	[A]	15		
Rated data		IEC	UL / CUL	CSA
Rated voltage	[V]	500	300	440
Nominal current / cross section	[A] / [mm ²]	17.5 / 1.5	15 / -	15 / -
Connection capacity		solid	stranded	Ferrule without/with plastic sleeve
1 conductor	[mm ²]	0.08 - 1.5	0.08 - 1.5	0.14 - 1.5
2 stranded conductors with a TWIN ferrule	[mm ²]	-	-	0.14 - 1.5
General data				
Stripping length	[mm]	10		

Description	No. of pos.	Color	Ordering data		
			Type	Order No.	Pcs. / Pkt.
Terminal block		gray	ST 1,5/S-QUATTRO	① 3213124	50
With potential distribution		blue			
		gray			
Ground terminal		green-yellow			

Description	No. of pos.	Color	Ordering data		
			Type	Order No.	Pcs. / Pkt.
STTB 1,5				① 3031157	50
STTB 1,5 BU				① 3031160	50
STTB 1,5-PV				② 3031526	50
STTB 1,5-PE				③ 3036013	50

Description	No. of pos.	Color	Accessories ¹⁾		
			Type	Order No.	Pcs. / Pkt.
Cover, width 2.2 mm		gray	D-ST 1,5/S-QUATTRO	3213166	50
Jumper					
	2	red	FBS 2-3,5	17.5 A 3213014	50
	3	red	FBS 3-3,5	17.5 A 3213027	50
	4	red	FBS 4-3,5	17.5 A 3213030	50
	5	red	FBS 5-3,5	17.5 A 3213043	50
	10	red	FBS 10-3,5	17.5 A 3213056	50

Description	No. of pos.	Color	Accessories ¹⁾	
			Type	Order No.
D-STTB 2,5				3030459