


## 4 mm<sup>2</sup> ST... spring-cage connection terminal blocks

### Feed-through, multi-conductor, and multi-level terminal blocks and ground terminals

**Notes:**  
 1) For additional accessories and technical data, see page 186.  
 For information on installation and using accessories for Ex applications, see page 602.



40 A, feed-through terminal block

Ex: 
  
 KEMA 00ATEX2129U / IECEx KEM 06.0050U

Technical data <sup>1)</sup>				
Width	Length	Height		
6.2	56	36.5 (NS 35/7,5)		
$I_{max}$ [A]	$U_{max}$ [V]	max. Ø [mm <sup>2</sup> ]	AWG (UL)	
40	800	0.08 - 6	28-10	
32 (FBS) / 24 (FBSR)				
IEC	UL / CUL	CSA	Ex	
800	600	600	550	
Nominal current / cross section	[A] / [mm <sup>2</sup> ]	32 / 4	30 / -	30 / 4


Ordering data			
Type	Order No.	Pcs. / Pkt.	
ST 4	3031364	50	①
ST 4 BU	3031377	50	①
ST 4-PE	3031380	50	②

Accessories <sup>1)</sup>		
D-ST 4	3030420	50

Dimensions	[mm]
Max. electrical data	
Max. bridge current	[A]
Rated data	
Rated voltage	[V]
Nominal current / cross section	[A] / [mm <sup>2</sup> ]

Description	Color
Terminal block	gray blue
Ground terminal	green-yellow

Cover, width 2.2 mm	gray
---------------------	------



40 A, feed-through terminal block, 3 connections

Ex: 
  
 KEMA 00ATEX2129U / IECEx KEM 06.0050U


Technical data <sup>1)</sup>				
Width	Length	Height		
6.2	71.5	36.5 (NS 35/7,5)		
$I_{max}$ [A]	$U_{max}$ [V]	max. Ø [mm <sup>2</sup> ]	AWG (UL)	
40	800	0.08 - 6	28-10	
32 (FBS) / 24 (FBSR)				
IEC	UL / CUL	CSA	Ex	
800	600	600	550	
Nominal current / cross section	[A] / [mm <sup>2</sup> ]	32 / 4	30 / -	30 / 4

Ordering data			
Type	Order No.	Pcs. / Pkt.	
ST 4-TWIN	3031393	50	①
ST 4-TWIN BU	3031403	50	①
ST 4-TWIN-PE	3031416	50	②

Accessories <sup>1)</sup>		
D-ST 4-TWIN	3030491	50

### Feed-through, multi-conductor, and multi-level terminal blocks and ground terminals

**Notes:**  
 1) For additional accessories and technical data, see page 186.  
 For information on installation and using accessories for Ex applications, see page 602.



40 A, feed-through terminal block, 4 connections

Ex: 
  
 KEMA 00ATEX2129U / IECEx KEM 06.0050U

Technical data <sup>1)</sup>				
Width	Length	Height		
6.2	87	36.5 (NS 35/7,5)		
$I_{max}$ [A]	$U_{max}$ [V]	max. Ø [mm <sup>2</sup> ]	AWG (UL)	
40	800	0.08 - 6	28-10	
32 (FBS)				
IEC	UL / CUL	CSA	Ex	
800	600	600	550	
Nominal current / cross section	[A] / [mm <sup>2</sup> ]	32 / 4	30 / -	28.5 / 4



Ordering data			
Type	Order No.	Pcs. / Pkt.	
ST 4-QUATTRO	3031445	50	①
ST 4-QUATTRO BU	3031458	50	①
ST 4-QUATTRO-PE	3031461	50	②

Accessories <sup>1)</sup>		
D-ST 4-QUATTRO	3030527	50

Dimensions	[mm]
Max. electrical data	
Max. bridge current	[A]
Rated data	
Rated voltage	[V]
Nominal current / cross section	[A] / [mm <sup>2</sup> ]

Description	Color
Terminal block	gray blue gray
Ground terminal	green-yellow

Cover, width 2.2 mm	gray
---------------------	------



37 A, feed-through terminal block, 4 connections, with interrupted current bar

Ex:

Technical data <sup>1)</sup>				
Width	Length	Height		
6.2	87	36.5 (NS 35/7,5)		
$I_{max}$ [A]	$U_{max}$ [V]	max. Ø [mm <sup>2</sup> ]	AWG (UL)	
37	800	0.08 - 6	28-10	
32 (FBS) / 24 (FBSR)				
IEC	UL / CUL	CSA	Ex	
800	600	-	-	
Nominal current / cross section	[A] / [mm <sup>2</sup> ]	28 / 4	30 / -	-

Ordering data			
Type	Order No.	Pcs. / Pkt.	
ST 4-QUATTRO-U	3038639	50	①

Accessories <sup>1)</sup>		
D-ST 4-QUATTRO	3030527	50