



16 (16) mm<sup>2</sup>, 10 A, lever-type fuse terminal block for 6.3 x 32 mm cartridge fuses



**Technical data**

Width	Length	Height NS 35/7,5	
10.2	79	60.5	
Width	Length	Height NS 32	
10.2	79	65.5	
$I_{max}$ [A]	$U_{max}$ [V]	Max. Ø [mm <sup>2</sup> ]	AWG (UL)
10 <sup>2</sup>	500 <sup>2</sup>	0.5 - 16	26-8
IEC 60947-7-3			
IEC	UL	CSA	IEC/ EN 60079-7
500 <sup>2</sup>	600	600	-
10 <sup>2</sup> / 1.5	10 / -	25 / -	-
16	-	-	-
20 - 6	26-8	26-8	-
Solid	Stranded	Ferrule without/with plastic sleeve	
0.5 - 16	0.5 - 16	0.5 - 10	0.5 - 10
0.5 - 4	0.5 - 4	0.5 - 4	-
-	-	-	0.5 - 6
10	10	-	-

G / 6,3 x 32  
12  
M4  
1.2 - 1.5  
PA  
V0

**Ordering data**

Type	$I_{max}$	Order No.	Pcs. / Pkt.
UK 6,3-HESI		3004171	50
UK 6,3-HESILED 24		3004265	50
UK 6,3-HESILA 250		3004249	50

**Accessories**

EB 2-10	63 A	0203153	100
VS		3004207	1
SZS 1,0X4,0 VDE		1205066	10

ZB 10 (see Catalog 5)  
ZB 8 (see Catalog 5)