



25 (25) mm<sup>2</sup>, 30 A, lever-type fuse terminal block for CLASS CC 10.3 x 38 mm



**Technical data**

Width	Length	Height NS 35/7,5	
18	81	65.5	
$I_{max}$ [A]	$U_{max}$ [V]	Max. Ø [mm <sup>2</sup> ]	AWG (UL)
30 <sup>2</sup> )	600 <sup>2</sup> )	1.5 - 25	-
IEC	UL	CSA	IEC/ EN 60079-7
600 <sup>2</sup> )	-	600	-
32 <sup>2</sup> ) / 25	-	30 / -	-
25	-	-	-
16 - 4	-	18-4	-
Solid	Stranded	Ferrule without/with plastic sleeve	
1.5 - 25	1.5 - 25	1.5 - 16	1.5 - 16
1.5 - 4	1.5 - 4	1.5 - 4	-
-	-	-	1.5 - 10
10	10	-	-
Class CC			
12			
M5			
2.5 - 3			
PA			
V0			

**Ordering data**

Type	$I_{max}$	Order No.	Pcs. / Pkt.
UK 10,3-CC HESI N		3048580	10
UK 10,3-CC HESILED N 600		3048616	10

**Accessories**

EB 2-18	76 A	3009300	50
EB 3-18	76 A	3009305	50
EB 56-18	76 A	3009299	5
EB 56-18/L1-L2-L3	76 A	3009367	5
TPN-UK		3003062	10
VS-UK 10,3-HESI N 2POL		3048532	10
VS-UK 10,3-HESI N 3POL		3048409	10
SF-SL 0,6X3,5-100 S-VDE		1212587	10
ZBF 10 (see Catalog 5)			