



Fuse terminal blocks

**Notes:**  
 1) If the fuse is faulty, the downstream circuit is not off load.  
 2) The current is determined by the fuse used, the voltage by the selected light indicator. Observe the maximum power dissipation, see phoenixcontact.net/products.



10 A, fuse terminal block for, 5 x 20 mm cartridge fuses



10 A, fuse terminal block, for 6.3 x 32 mm cartridge fuses



Technical data				
Width	Length	Height NS 35/7,5		
12	86.5	56.5		
I <sub>max</sub> [A]	U <sub>max</sub> [V]	max. Ø [mm <sup>2</sup> ]	AWG (UL)	
10 <sup>2</sup>	800 <sup>2</sup>	0.5 - 10	20-8	
IEC 60947-7-3				
IEC	UL	CSA	IEC/EN 60079-7	
Rated voltage [V]	800 <sup>2</sup>	600	-	-
Nominal current / cross section [A] / [mm <sup>2</sup> ]	10 <sup>2</sup> / 1.5	20 / -	-	-
Rated cross section [mm <sup>2</sup> ]	6	-	-	-
Cross section range AWG	20 - 8	20-8	-	-
Connection capacity	solid	stranded	Ferrule without/with plastic sleeve	
	1 conductor [mm <sup>2</sup> ]	2 stranded conductors with a TWIN ferrule [mm <sup>2</sup> ]	0.5 - 10	0.5 - 6
General data	Fuse type / dimensions - / [mm]	G / 5 x 20		
Stripping length [mm]	12	12		
Insulating material	PA	PA		
Inflammability class according to UL 94	V0	V0		



Technical data				
Width	Length	Height NS 35/7,5		
12	86.5	56.5		
I <sub>max</sub> [A]	U <sub>max</sub> [V]	max. Ø [mm <sup>2</sup> ]	AWG (UL)	
10	800	0.5 - 10	20-8	
IEC 60947-7-3				
IEC	UL	CSA	IEC/EN 60079-7	
Rated voltage [V]	800	600	-	-
Nominal current / cross section [A] / [mm <sup>2</sup> ]	10 / 1.5	20 / -	-	-
Rated cross section [mm <sup>2</sup> ]	6	-	-	-
Cross section range AWG	20 - 8	20-8	-	-
Connection capacity	solid	stranded	Ferrule without/with plastic sleeve	
	1 conductor [mm <sup>2</sup> ]	2 stranded conductors with a TWIN ferrule [mm <sup>2</sup> ]	0.5 - 10	0.5 - 6
General data	Fuse type / dimensions - / [mm]	G / 6,3 x 32		
Stripping length [mm]	12	12		
Insulating material	PA	PA		
Inflammability class according to UL 94	V0	V0		

Description	No. of pos.	Color
Fuse terminal block for 12 - 30 V DC, 0.7 - 2.4 mA <sup>1)</sup>		black
Fuse terminal block, 110 - 250 V AC/DC, 0.2 - 0.9 mA <sup>1)</sup>		black
Fuse terminal block, with indicating pin		black

Ordering data				
Type	I <sub>max</sub>	Order No.	Pcs. / Pkt.	
ZFK 6-DREHSI (5X20)		3025040	25	
ZFK 6-DREHSILED 24 (5X20)		3025600	25	
ZFK 6-DREHSILA 250 (5X20)		3025590	25	
ZFK 6-DREHSI/K (5X25)		3029457	25	

Ordering data				
Type	I <sub>max</sub>	Order No.	Pcs. / Pkt.	
ZFK 6-DREHSI (6,3X32)		3025273	25	
ZFK 6-DREHSILED 24 (6,3X32)		3025587	25	
ZFK 6-DREHSILA 250 (6,3X32)		3025574	25	

Fixed bridge, isolated		
	10	silver
Test plug metal part, 2.3 mm Ø		silver
Insulating sleeve, for MPS metal part		red
Screwdriver		
Center and lateral groove marking		

Accessories				
FBI 10-12	57 A	0203454	10	
MPS-MT		0201744	10	
MPS-IH RD		0201676	10	
SZF 2-0,8X4,0		1204520	10	
UC-TMF 12, UCT-TMF 12 or ZBF 12 (see Catalog 5)				

Accessories				
FBI 10-12	57 A	0203454	10	
SZF 2-0,8X4,0		1204520	10	
UC-TMF 12, UCT-TMF 12 or ZBF 12 (see Catalog 5)				