



16 (16) mm<sup>2</sup>, 76 A, connection terminal blocks



35 (35) mm<sup>2</sup>, 125 A, connection terminal blocks



**Technical data**

Width	Length	Height	
9.8	23.7	29	
I <sub>max</sub> [A]	U <sub>max</sub> [V]	max. Ø [mm <sup>2</sup> ]	AWG (UL)
76	300	1.5 - 16	18-6
IEC	UL	CSA	IEC/ EN 60079-7
300	300	-	-
76 / 16	50 / -	65 / -	-
16	-	-	-
16 - 6	18-6	18-6	-
solid	stranded	ferrule without/with plastic sleeve	
1.5 - 16	1.5 - 16	1.5 - 16	1.5 - 16
1.5 - 6	1.5 - 6	1.5 - 6	-
-	-	-	1.5 - 10

16  
M5  
2.5 - 3  
PA  
V2

**Technical data**

Width	Length	Height	
14.3	27	39	
I <sub>max</sub> [A]	U <sub>max</sub> [V]	max. Ø [mm <sup>2</sup> ]	AWG (UL)
125	300	2.5 - 35	18-2
IEC / EN	UL	CSA	IEC/ EN 60079-7
300	300	-	-
125 / 35	115 / -	135 / -	-
35	-	-	-
14 - 2	18-2	18-2	-
solid	stranded	ferrule without/with plastic sleeve	
2.5 - 35	2.5 - 35	2.5 - 35	2.5 - 35
1.5 - 16	1.5 - 16	1.5 - 16	-
-	-	-	1.5 - 10

16  
M6  
3.2 - 3.7  
PA  
V2

**Ordering data**

Type	I <sub>max</sub>	Order No.	Pcs. / Pkt.
AKG 16 BK		0423030	50
AKG 16 GNYE		0423027	50
AKG 16 BU		0423014	50
AK 16		0404033	50

**Ordering data**

Type	I <sub>max</sub>	Order No.	Pcs. / Pkt.
AKG 35 BK		0424039	50
AKG 35 GNYE		0424026	50
AKG 35 BU		0424013	50
AK 35		0404046	50