



Double-level terminal blocks

Notes:

<sup>1)</sup> For additional accessories and technical data, see page 166.



24 A, double-level terminal block

20 A, double-level terminal block, both levels can be bridged



Technical data <sup>1)</sup>				
Width	Length	Height		
5.2	67.5	42.5 (NS 35/7,5) / 42 (NS 15)		
I <sub>max.</sub> [A]	U <sub>max.</sub> [V]	max. Ø [mm <sup>2</sup> ]	AWG (UL)	
24	500	0.14 - 2.5	26-14	
Max. bridge current	[A]	20		
Rated data	IEC	UL / CUL	CSA	Ex
Rated voltage	500	600	-	-
Nominal current / cross section	[A] / [mm <sup>2</sup> ]	17.5 / -	-	-
Cross section range	AWG	26 - 14	-	-
Connection capacity	solid	stranded	Ferrule without/with plastic sleeve	
1 conductor	[mm <sup>2</sup> ]	0.14 - 2.5	0.14 - 1.5	0.14 - 1.5
General data	Stripping length [mm] 9			

Ordering data			
Description	No. of pos.	Color	
Terminal block		gray	
With potential distribution		gray	

Type	Order No.	Pcs. / Pkt.
MZFVK 1,5	3029813	50
MZFVK 1,5-PV	3029826	50

Accessories <sup>1)</sup>			
Type	Order No.	Pcs. / Pkt.	
D-MZFVK 1,5	3029839	50	
TS-KK 3	2770215	50	
FBRI 2-5 N	3000227	10	20 A
FBRI 3-5 N	3000201	10	20 A
FBRI 10-5 N	2770642	10	20 A
SZF 1-0,6X3,5	1204517	10	

UC-TMF 5, UCT-TMF 5 or ZBF 5 (see Catalog 5)



Technical data <sup>1)</sup>				
Width	Length	Height		
5.2	85	42.5 (NS 35/7,5) / 42 (NS 15)		
I <sub>max.</sub> [A]	U <sub>max.</sub> [V]	max. Ø [mm <sup>2</sup> ]	AWG (UL)	
20	500	0.14 - 2.5	26-14	
Max. bridge current	[A]	17.5		
Rated data	IEC	UL / CUL	CSA	Ex
Rated voltage	500	600	-	-
Nominal current / cross section	[A] / [mm <sup>2</sup> ]	17.5 / 1.5	15 / -	-
Cross section range	AWG	26 - 14	-	-
Connection capacity	solid	stranded	Ferrule without/with plastic sleeve	
1 conductor	[mm <sup>2</sup> ]	0.14 - 2.5	0.14 - 1.5	0.14 - 1.5
General data	Stripping length [mm] 9			

Ordering data			
Description	No. of pos.	Color	
Terminal block		gray	
With potential distribution		gray	

Type	Order No.	Pcs. / Pkt.
MZFKKB 1,5	3005714	50

Accessories <sup>1)</sup>			
Type	Order No.	Pcs. / Pkt.	
D-MZFKKB 1,5	3024630	50	
TS-KK 3	2770215	50	
FBRI 2-5 N	3000227	10	20 A
FBRI 3-5 N	3000201	10	20 A
FBRI 10-5 N	2770642	10	20 A
SZF 1-0,6X3,5	1204517	10	

UC-TMF 5, UCT-TMF 5 or ZBF 5 (see Catalog 5)

Lateral groove marking