


Terminal blocks - CLIPLINE complete


2.5 mm² ST... spring-cage connection terminal blocks

Feed-through, multi-conductor, and multi-level terminal blocks and ground terminals

Notes:
 1) For additional accessories and technical data, see page 170.
 For information on installation and using accessories for Ex applications, see page 602.



26 A, double-level terminal block



32 A, double-level ground terminal



Ex: Ex Ex
 KEMA 00ATEX2052U / IECEx KEM 06.0051U

Technical data¹⁾

Dimensions	[mm]
Width	5.2
Length	67.5
Height	47.5 (NS 35/7,5)
Max. electrical data	
$I_{max.}$ [A]	26
$U_{max.}$ [V]	500
max. Ø [mm ²]	0.08 - 4
AWG (UL)	28-12
24 (FBS) / 17.5 (FBSR)	
Rated data	
IEC	UL / CUL
CSA	Ex
500	600
300	440
Rated voltage [V]	500
Nominal current / cross section [A] / [mm ²]	22 / 2.5

Width	5.2	Length	67.5	Height	47.5 (NS 35/7,5)
$I_{max.}$ [A]	26	$U_{max.}$ [V]	500	max. Ø [mm ²]	0.08 - 4
AWG (UL)	28-12	24 (FBS) / 17.5 (FBSR)			
IEC	UL / CUL	CSA	Ex		
500	600	300	440		
Rated voltage [V]	500				
Nominal current / cross section [A] / [mm ²]	22 / 2.5	20 / -	20 / -	19.5 / 2.5	

Ordering data

Description	Color
Terminal block	gray
	blue
With potential distribution	gray
	blue
Ground terminal	green-yellow
Terminal block	gray-yellow-green
	gray
	gray

Type	Order No.	Pcs. / Pkt.
STTB 2,5	① 3031270	50
STTB 2,5 BU	① 3031283	50
STTB 2,5-PV	② 3031539	50
STTB 2,5-PV BU	② 3035108	50
STTB 2,5-PE	③ 3036026	50

Accessories¹⁾

Cover, width 2.2 mm	gray
----------------------------	------

D-STTB 2,5	3030459	50
-------------------	---------	----



Width	5.2	Length	67.5	Height	47.5 (NS 35/7,5)
$I_{max.}$ [A]	32	$U_{max.}$ [V]	500	max. Ø [mm ²]	0.08 - 4
AWG (UL)	28-12	20 (FBS) / 17.5 (FBSR)			
IEC	UL / CUL	CSA	Ex		
500	300	300	-		
Rated voltage [V]	500				
Nominal current / cross section [A] / [mm ²]	22 / 2.5	20 / -	20 / -		

Technical data¹⁾



Type	Order No.	Pcs. / Pkt.
STTB 2,5-PE/L	① 3036314	50
STTB 2,5-PE/N	① 3036327	50
STTB 2,5-L/N	② 3036330	50

Accessories¹⁾



D-STTB 2,5	3030459	50
-------------------	---------	----

Feed-through, multi-conductor, and multi-level terminal blocks and ground terminals

Notes:
 1) For additional accessories and technical data, see page 170.



26 A, feed-through terminal block, 3 connections per level



26 A, feed-through terminal block, with equipotential bonding



Width	5.2	Length	91.5	Height	47.5 (NS 35/7,5)
$I_{max.}$ [A]	26	$U_{max.}$ [V]	500	max. Ø [mm ²]	0.08 - 4
AWG (UL)	28-12	20 (FBS) / 17.5 (FBSR)			
IEC	UL / CUL	CSA	Ex		
500	600	300	-		
Rated voltage [V]	500				
Nominal current / cross section [A] / [mm ²]	22 / 2.5	20 / -	20 / -		

Ordering data

Description	Color
Terminal block	gray
	blue
	gray
Ground terminal	green-yellow

Type	Order No.	Pcs. / Pkt.
STTB 2,5-TWIN	① 3038516	50
STTB 2,5-TWIN BU	① 3038529	50
STTB 2,5-TWIN-PE	② 3038532	50

Accessories¹⁾

Cover, width 2.2 mm	gray
----------------------------	------

D-STTB 2,5-TWIN	3038558	50
------------------------	---------	----



Width	5.2	Length	91.5	Height	47.5 (NS 35/7,5)
$I_{max.}$ [A]	26	$U_{max.}$ [V]	500	max. Ø [mm ²]	0.08 - 4
AWG (UL)	28-12	20 (FBS) / 17.5 (FBSR)			
IEC	UL / CUL	CSA	Ex		
500	600	300	-		
Rated voltage [V]	500				
Nominal current / cross section [A] / [mm ²]	22 / 2.5	20 / -	20 / -		

Ordering data

Type	Order No.	Pcs. / Pkt.
STTB 2,5-TWIN-PV	① 3038545	50

Accessories¹⁾

D-STTB 2,5-TWIN	3038558	50
------------------------	---------	----