A200/B100 Heater

FH27

UPC:786678629681

Dimensions:

Height: X Length: X Width: X

Notes:Select heater coils based on full load current(FLA) shown on motor nameplate. Heater coils are rated to protect 40 degree C rise and a service factor of 1.15, Single-Phase requires 2 heaters, Three-Phase Requires 3 heaters

Warranties:

 Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.

Specifications:

 Special Features: Used with Starter Sizes 0,1, and 2

• Type: A200/B100 Heater

• Design: NEMA

 Full Load Current Range: Ambient 2.59-2.83, 3.00-3.28A, Non-Comp 2.40-2.63 2.93-3.21A

Overload Relay: Type A and B
Trip Type: Thermal and Fast Trip

Supporting documents:

- Eatons Volume 5-Motor Control and Protection
- Instructions for A200, A210, A250 size 6, twoor three-pole non-reversing or reversing motor controllers
- Eaton Specification Sheet FH27

Certifications:

- UL Listed
- CSA Certified



P	ro	duc	t co	mnli	iance:	No	Data
	ı	uuc		шрп	iaiice.	INO	Data

© 2016 Eaton. All rights reserved.