# A200/B100 Heater

**FH39** 

UPC:786678670034

### **Dimensions:**

Height: XLength: XWidth: X

**Notes:**Select heater coils based on full load current(FLA) shown on motor nameplate. Heater coils are rated to protect 40 degree C rise and a service factor of 1.15, Single-Phase requires 2 heaters, Three-Phase Requires 3 heaters

#### Warranties:

 Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.

# **Specifications:**

 Special Features: Used with Starter Sizes 0,1, and 2

• Type: A200/B100 Heater

• Design: NEMA

• Full Load Current Range: Ambient 7.9-8.5, 9.1-9.9A, Non-Comp 7.3-7.9, 8.8-9.7A

Overload Relay: Type A and BTrip Type: Thermal and Fast Trip

# **Supporting documents:**

- Eatons Volume 5-Motor Control and Protection
- Instructions for A200, A210, A250 size 6, twoor three-pole non-reversing or reversing motor controllers
- Eaton Specification Sheet FH39

#### **Certifications:**

- UL Listed
- CSA Certified



P	ro	duc	t co	mnli	iance:	No	Data
	ı	uuc		шрп	iaiice.	INO	Data

© 2016 Eaton. All rights reserved.