A200 Heater

FH73

UPC:786678670638

Dimensions:

Height: XLength: XWidth: X

Notes:Select heater coils based on full load current(FLA) shown on motor nameplate. Heater coils are rated to protect 40 degree C rise and a service factor of 1.15, Single-Phase requires 2 heaters, Three-Phase Requires 3 heaters

Warranties:

 Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.

Specifications:

 Special Features: Used with A200 Starter Sizes 3 &4, 3-Phase Only

Type: A200 HeaterDesign: NEMA

• Full Load Current Range: Ambient 20.9-22.

9A, Non-Comp 19.2-21.1AOverload Relay: Type A and BTrip Type: Thermal and Fast Trip

Supporting documents:

- Eatons Volume 5-Motor Control and Protection
- Instructions for A200, A210, A250 size 6, twoor three-pole non-reversing or reversing motor controllers
- Eaton Specification Sheet FH73

Certifications:

- CSA Certified
- UL Listed



P	ro	du	ct	COI	nn	lian	ce:	Nο	Data
	10	u	UL	COI	IIP.	IIGI	UC.	1 40	Data

© 2016 Eaton. All rights reserved.