A200 Heater

FH71

UPC:786678670713

Dimensions:

Height: XLength: XWidth: X

Notes:Select heater coils based on full load current(FLA) shown on motor nameplate. Heater coils are rated to protect 40 degree C rise and a service factor of 1.15, Single-Phase requires 2 heaters, Three-Phase Requires 3 heaters

Warranties:

 Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.

Specifications:

 Special Features: Used with A200 Starter Sizes 3 &4, 3-Phase Only

Type: A200 HeaterDesign: NEMA

• Full Load Current Range: Ambient 17.2. 18.9A, Non-Comp 16.0-17.4A

Overload Relay: Type A and B
Trip Type: Thermal and Fast Trip

Supporting documents:

- Eatons Volume 5-Motor Control and Protection
- Instructions for A200, A210, A250 size 6, twoor three-pole non-reversing or reversing motor controllers
- Eaton Specification Sheet FH71

Certifications:

- CSA Certified
- UL Listed



| P | ro | du | ct | COI | nn | lian | ce: | Nο | Data |
|---|----|----|----|-----|------|------|-----|------|------|
| | 10 | u | UL | COI | IIP. | IIGI | UC. | 1 40 | Data |

© 2016 Eaton. All rights reserved.