

PAR
Indoor Flood



Part #	Description (HAL Wattage)	Bulb Shape	Bulb Base	Colour (Temp.)	Beam Degree	Lumens	Hours	Dim.	E-Star
431916	HAL 50W (50W)	PAR16	Med. Base	CLR (2850K)	28°	450	3000	Y	
424531	HAL 50W (39W)	PAR20	Med. Base	CLR (2850K)	25°	480	1100	Y	
424556	HAL 50W 4Pk (39W)	PAR20	Med. Base	CLR (2850K)	25°	480	1100	Y	
456772	HAL 50W Spot (39W)	PAR20	Med. Base	CLR (2850K)	10°	480	1100	Y	
149534	HAL 50W 2Pk (50W)	PAR20	Med. Base	CLR (2850K)	28°	520	3000	Y	
160036	HAL 50W (50W)	PAR20	Med. Base	CLR (2850K)	28°	520	3000	Y	
238758	HAL 50W 4Pk (50W)	PAR20	Med. Base	CLR (2850K)	28°	520	3000	Y	
456764	HAL 50W (39W)	PAR30L	Med. Base	CLR (2850K)	25°	500	1100	Y	
424549	HAL 75W (50W)	PAR30L	Med. Base	CLR (2850K)	25°	960	4200	Y	
424572	HAL 75W 2Pk (53W)	PAR30L	Med. Base	CLR (2850K)	25°	920	1100	Y	