LED Wall Pack

LED Wall Pack 70W - Adjustable 7700 Lumens 4000K





| Electrical | |
|-------------------------------|-----------------------------|
| Watt | 70 |
| Voltage | 100-277V |
| Power Factor | >0.9 |
| Min. Start Temperature | -31°F |
| Max. Operating Temperature | 122°F |
| Light | |
| Initial Lumens | 7700 |
| Lumens per Watt | 110 |
| Color Temperature | 4000K |
| Color Rendering (CRI) | >80 |
| Beam Angle | V:105±10° H:85±10° |
| Agency Approvals | |
| DLC | Yes |
| CSA | No |
| FCC | Yes |
| ETL | Yes |
| Product Details | |
| Housing Material | Aluminum |
| Lens Material | Glass |
| Warranty | 5 years, 10 year limited |
| Rated Life | 50,000 hours |

PRODUCT DESCRIPTION

The EarthTronics adjustable wall pack can be locked in to any angle ranging from 0° to 90° providing exterior security illumination where required. The durable die cast aluminum housing is powder coated to maintain the fixture appearance for several years. This 70 watt wall pack operates at 110 lumens per watt efficiency and provides 7700 lumens. 4000K color of light and the high 80+ CRI provide bright illumination. Accepts 100 – 277 volt AC power supply. The long 50,000 hour is backed up with a 10 year limited warranty. The wall pack fixture requires a properly anchored UL recognized junction box for proper installation.

PRODUCT FEATURES

- High Quality Die Cast Aluminum Housing
- · Durable bronze powder coat finish
- 0 90° adjustable beam angle locks in position
- · Suited for wall mounting to provide a wide flood area
- · IP65 rated for wet location use
- Contemporary design compliments building exteriors
- · DLC listed
- 120-277 volt constant current driver
- 50,000 hour rated life L70

Order Code: WP04A670040BK1

Model #: WP04A670040

DLC Product ID: PHVMJVVV

DIMENSIONS:

Diameter: 9.72 inches

Nominal Length: 10.51 inches

WEIGHT: 7.28 lbs

CAUTION: If the fixture is to be removed or replaced, please ensure that they electricity is switched off and that the fitting is cool before touching it





