

Flex-Plus Blue ENT



Flex-Plus Blue ENT is a nonmetallic flexible raceway for use in walls, floors and non-plenum ceilings. It's lightweight, hand bendable and free from sharp edges, which reduces installation time and saves money.

- Ideal storage conditions down to -20 °C (See [page 73](#) for technical information.)

Options

- Sizes ½ in. through 2 in.
- Colours can designate different voltages
- Yellow colour for communication circuits and signaling cable
- Red colour for fire alarm circuits
- Blue colour for power circuits

Standard stock – Reels



Cat. no.	Size (in.)	Colour	Nom. I.D. (in.)	Nom. O.D. (in.)	Pull tape	Min. bend radius	Reel type (W=Wood)	Reel length (ft.)	Reel wt. (lb)	Wt. per 100 ft. (lb)
1205AKC-001	½	Blue	0.56	0.84	Empty	36 x 24	W	1,500	40	10
1207AAC-001	¾	Blue	0.76	1.05	Empty	36 x 24	W	1,000	40	14
12008C-750	1	Blue	1.00	1.315	Empty	36 x 24	W	750	40	20
12009C-750	1¼	Blue	1.402	1.66	Empty	48 x 32	W	750	90	19
12009C-500	1¼	Blue	1.402	1.66	Empty	48 x 32	W	500	90	19
12010C-750	1½	Blue	1.554	1.90	Empty	48 x 32	W	750	90	39
12011C-500	2	Blue	2.030	2.375	Empty	48 x 32	W	500	90	32
12011C-225	2	Blue	2.030	2.375	Empty	48 x 32	W	225	90	32

1¼ in. – 2 in. available in yellow and red, made to order; contact your regional sales office.

Standard stock – Coils

Cat. no.	Size (in.)	Colour	Nom. I.D. (in.)	Nom. O.D. (in.)	Pull Tape	Min. bend radius	Coil length (ft.)	Wt. per 100 ft. (lb)
12005C-200	½	Blue	0.56	0.84	Empty	6	200	10
12005C-370	½	Blue	0.56	0.84	Empty	6	370	10
12007C-100	¾	Blue	0.76	1.05	Empty	6	100	14
12007C-240	¾	Blue	0.76	1.05	Empty	6	240	14
12008C-160	1	Blue	1.00	1.315	Empty	6	160	22
12009C-500C	1¼	Blue	1.402	1.66	Empty	7	500	19
12010C-300C	1½	Blue	1.554	1.90	Empty	8¼	300	39
12011C-225C	2	Blue	2.030	2.375	Empty	9½	225	32

NOTE: The solid blue colour of ENT conduit is a registered trademark of Carlon.

ENT may show colour deterioration in direct sunlight when stored outdoors over an extended period of time. It is suggested that all ENT products not be stored outside.