

## Eaton XT IEC contactor

**XTCE050D00A**

### Dimensions:

- **Height:** 2 IN
- **Length:** 6 IN
- **Width:** 4.75 IN

**Weight:**2.12 LB

**Notes:**Screw terminals (6-65A); 5 mm (80-150A);  
no lugs (185-2000A)

**Warranties:** No Data

### Specifications:

- **Amperage Rating:** 50A
- **Coil:** 110V 50 Hz, 120V 60 Hz
- **Coil Voltage:** 110 Vac 50 Hz, 120 Vac, 60 Hz
- **Contact Configuration:** 0NO-0NC
- **Frame Size:** 55 mm
- **Frequency Rating:** 50-60 Hz
- **Max Hp Rating:** 3, 7.5, 10/ 15, 20, 40, 50 hp  
(1/3PH @115,200,230/200,230,460,575 V)
- **Number Of Poles:** Three-pole
- **Operation:** Non-reversing
- **Series:** XT IEC series
- **Terminals:** Screw terminals
- **Type:** Full voltage non-reversing contactor

### Supporting documents:

- [Eatons Volume 5-Motor Control and Protection](#)
- [XTCE\\_D 3D Inventor](#)
- [XTCE\\_D 2D Drawing Xchange](#)
- [XTCE\\_D AutoCAD 2D Footprint](#)
- [XTCE\\_D 3D Model Xchange](#)
- [XTCE\\_D 2D PDF](#)
- [Global Data Sheet - XTCE050D00A](#)
- [Eaton Specification Sheet - XTCE050D00A](#)

### Certifications:

- UL Listed



- CSA Certified
- IEC 60947
- EN 60947

**Product compliance:**

- RoHS Compliant
- CE Marked

---

© 2016 Eaton. All rights reserved.