# UNIPAK, Low Voltage Fixed Capacitor Banks

#### **1063PMURF**

UPC:782116059072

#### **Dimensions:**

Height: 17.3 INLength: 5.254 INWidth: 8.5 IN

Weight:20 LB

**Notes:**Multiply the 240V kVAR rating by 0.75 to calculate the kVAR value at 208V.

### Warranties:

• Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.

#### **Specifications:**

• Type: UNIPAK

Amperage Rating: 9.80AEnclosure: NEMA 1, 3R

 Enclosure Material: 14 ga. steel finished w/durable powder coat finish

• Frame Size: A1

• **Fuse Type:** Three midget-type fuses with 100,000 ampere interrupting capacity

 Indicator: Red, neon blown-fuse indicating lights are protected by transparent weatherproof guard

• Phase: Three-phase

 Product Category: Low Voltage Fixed Capacitor Banks

• Protection: Three fuses, three lights

• Rating: 10 kVAR

• Voltage Rating: 600V



## **Supporting documents:**

- Eatons Volume 3-Power Distribution and Control Assemblies
- Eaton Specification Sheet 1063PMURF

## **Certifications:**

- CSA Certified
- UL Listed

Product compliance: No Data

\_\_\_\_\_

© 2016 Eaton. All rights reserved.