

## Eaton E65 SM compact photoelectric sensor

**E65-SMPR3-GDD**

**UPC:**782114786185

### Dimensions:

- **Height:** 1.29 IN
- **Length:** 2.17 IN
- **Width:** 1.63 IN

**Weight:**.0688 LB

**Notes:**For complete system; order sensor and retroreflector. Retroreflector not included

### Warranties:

- 3 year

### Specifications:

- **Connection:** 4 Pin Dual Key Micro Connector
- **Contact Rating:** 200 mA DC NPN / 200 mA AC 3 - Wire
- **Cable Type:** PVC
- **Contact Configuration:** AC: L1 Switched, DC: NPN Open Collector
- **Enclosure Material:** Lens: polycarbonate cable jacket: PVC body: Cyclooy
- **Environmental Rating:** NEMA 1,3,4,4X,6,6P,12,13, IP68, IP69K
- **Input Voltage:** 18–264 Vac/18–50 Vdc
- **Led Indicators:** Green power on, red output status, orange marginal gain
- **Maximum Ac Current:** 200 mA
- **Operating Mode:** Polarized Retroreflective
- **Operating Temperature:** -13° to 131°F (-25° to 55°C)
- **Switch Type:** Photoelectric

### Supporting documents:

- [Eaton's Volume 8-Sensing Solutions](#)



- [Test the Best Photoelectric Sensors: SM Series](#)
- [Eaton Specification Sheet - E65-SMPR3-GDD](#)

**Certifications:**

- cUL Listed
- UL Listed

**Product compliance:**

- CE Marked

---

© 2016 Eaton. All rights reserved.