

## Contactor Accessory - Auxiliary Contact

### XTCEXFACC11

#### Dimensions:

- **Height:** 1.5 IN
- **Length:** 1.5 IN
- **Width:** 2.5 IN

#### Weight:.1 LB

**Notes:**Interlocked opposing contacts, to IEC/EN 60947-5-1 Annex L (positively driven), within the auxiliary contact modules (not NOE and NCL contacts) and between the auxiliary contacts and built-in contacts of the XTRE control relays.

#### Warranties: No Data

#### Specifications:

- **Type:** Contactor Accessory - Auxiliary Contact
- **Used With:** XTRE control relays
- **Conventional Thermal Current:** 16A
- **Contact Configuration:** 1NO-1NC
- **Number Of Poles:** Two-pole
- **Quantity:** 5
- **Rated Operational Current:** 6A at 220/230/240V; 3A at 380/400/415V; 1.5A at 500V
- **Terminals:** Spring cage terminals

#### Supporting documents:

- [Eaton's Volume 10-Enclosed Control](#)
- [Global Data Sheet - XTCEXFACC11](#)
- [Eaton Specification Sheet - XTCEXFACC11](#)

#### Certifications:

- IEC 60947
- EN 60947
- UL Listed
- CSA Certified



**Product compliance:**

- CCC Marked
- ATEX Compliant
- CE Marked

---

© 2016 Eaton. All rights reserved.