

XT IEC Bimetallic Overload Relay

XTOB070GC1

Dimensions:

- Height: X
- Length: X
- Width: X

Warranties: No Data

Specifications:

- Contact Configuration: 1NO-1NC
- Frame Size: 90 mm
- Mounting: Direct
- Overload Range: 50-70A
- Trip Type: 10A
- Type: XT IEC Bimetallic Overload Relay
- Used With: 80-170A contactor

Supporting documents:

- [C440 Electronic Overload Relay](#)
- [Eaton's Volume 5-Motor Control and Protection](#)
- [XTOB_GC1 2D PDF](#)
- [XTOB_GC1 3D Model Xchange](#)
- [XTOB_GC1 AutoCAD 2D Footprint \(mm\)](#)
- [XTOB_GC1 AutoCAD 2D Footprint](#)
- [XTOB_GC1 2D Drawing Xchange](#)
- [XTOB_GC1 3D Inventor](#)
- [Global Data Sheet - XTOB070GC1](#)
- [Eaton Specification Sheet - XTOB070GC1](#)

Certifications:

- UL Listed
- CSA Certified
- IEC 60947
- EN 60947

Product compliance:

- CE Marked
- ATEX Compliant



- RoHS Compliant

© 2016 Eaton. All rights reserved.