

Eaton C22 compact pushbutton

C22-WRKV-K10

Dimensions:

- **Height:** 2.83 IN
- **Length:** 1.17 IN
- **Width:** 1.17 IN

Weight: .06 LB

Notes: Maintained pushbuttons can be converted in the field to momentary operation by switching the locking ring, which is accessible through the side of the operator body.

Warranties:

- Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.

Specifications:

- **Type:** Selector Switch
- **Action:** Maintained, 60° V Position
- **Actuator:** Knob
- **Bezel:** Silver
- **Button Color:** Black/White
- **Color:** Black/ White
- **Contact Configuration:** 1NO
- **Illumination:** Non-Illuminated
- **Number Of Positions:** 3-position
- **Size:** 22.5 mm
- **Series:** C22

Supporting documents:

- [Eatons Volume 7-Logic Control, Operator Interface and Connectivity Solutions](#)
- [C22\(S\)-W\(R\)KV 2D Drawing Xchange](#)
- [C22\(S\)-W\(R\)KV AutoCAD 2D Footprint](#)
- [C22\(S\)-W\(R\)KV 3D Model Xchange](#)
- [C22\(S\)-W\(R\)KV 3D Inventor](#)



- [C22\(S\)-W\(R\)KV AutoCAD 2D Footprint \(mm\)](#)
- [C22\(S\)-W\(R\)KV 2D PDF](#)
- [C22 Pilot Devices](#)
- [Eaton Specification Sheet - C22-WRKV-K10](#)

Certifications:

- EN 60947
- IEC 60947
- UL Listed
- CSA Certified

Product compliance:

- DIN VDE 0600