

## Eaton XT IEC contactor

XTCE015B01B

### Dimensions:

- **Height:** 2 IN
- **Length:** 3.25 IN
- **Width:** 3 IN

**Weight:** .5070632 LB

**Notes:** Screw terminals (6-65A); 5 mm (80-150A);  
no lugs (185-2000A)

**Warranties:** No Data

### Specifications:

- **Amperage Rating:** 15A
- **Coil Voltage:** 220 Vac 50 Hz, 240 Vac 60 Hz
- **Contact Configuration:** 1NC
- **Frequency Rating:** 50-60 Hz
- **Max Hp Rating:** 1, 2, 3/ 5, 5, 10, 10 hp (1/3PH @ 115,200,230/200,230,460,575 V)
- **Number Of Poles:** Three-pole
- **Operation:** Non-reversing
- **Series:** XT IEC series
- **Terminals:** Screw terminals
- **Type:** Full voltage non-reversing contactor

### Supporting documents:

- [Eatons Volume 5-Motor Control and Protection](#)
- [XTCE\\_B 3D Model Xchange](#)
- [XTCE\\_B AutoCAD 2D Footprint](#)
- [XTCE\\_B 2D Drawing Xchange](#)
- [XTCE\\_B 3D Inventor](#)
- [XTCE\\_B 2D PDF](#)
- [Eaton Specification Sheet - XTCE015B01B](#)
- [Global Data Sheet - XTCE015B01B](#)

### Certifications:

- UL Listed
- CSA Certified
- IEC 60947



- EN 60947

**Product compliance:**

- RoHS Compliant
- CE Marked

---

© 2016 Eaton. All rights reserved.