

## Eaton SL7 stacklight acoustic module

### SL7-AP24

#### Dimensions:

- **Height:** X
- **Length:** X
- **Width:** X

#### Warranties:

- 2 year

#### Specifications:

- **Type:** 70 mm
- **Decibel:** 100 dB
- **Environmental Rating:** IP66
- **Frequency Rating:** 2800 Hz
- **Accessories:** Internal DIP switch, internal potentiometer
- **Color:** Black
- **Enclosure:** UL type 4, 4X, 13
- **Model:** Continuous or pulsed tone, adjustable
- **Quantity:** -1
- **Rated Operational Current:** 92A max.
- **Series:** SL7
- **Voltage Rating:** 24 Vac/Vdc

#### Supporting documents:

- [Eaton's Volume 7-Logic Control, Operator Interface and Connectivity Solutions](#)
- [Eaton Specification Sheet - SL7-AP24](#)

#### Certifications:

- CSA Certified
- cULus Listed
- UL Listed
- UL 508
- CSA Std. C22.2 No. 14-10
- UL Listed file E29184
- CSA Std. C22.2 No. 94-91



- CSA Class No. NKCR7
- IEC Rated

**Product compliance:**

- CE Marked

---

© 2016 Eaton. All rights reserved.