

Eaton XT IEC mini contactor

XTMR9A21A

UPC:782116884339

Dimensions:

- **Height:** 5 IN
- **Length:** 5.25 IN
- **Width:** 5.75 IN

Weight:1.2 LB

Notes:Screw terminals (6-65A); 5 mm (80-150A);
no lugs (185-2000A)

Warranties:

- 1 year

Specifications:

- **Amperage Rating:** 8.80A
- **Coil:** 110v 50 Hz, 120V 60 Hz
- **Coil Voltage:** 110 Vac 50 Hz, 120 Vac, 60 Hz
- **Contact Configuration:** 2NO-2NO
- **Frame Size:** 45 mm mini
- **Frequency Rating:** 50-60 Hz
- **Max Hp Rating:** 0.5, 1, 1.5/ 2, 3, 5, 5 hp (1/3PH @115,200,230/200,230,460,575 V)
- **Number Of Poles:** Three-pole
- **Operation:** Non-reversing
- **Series:** XT IEC series
- **Terminals:** Screw terminals
- **Type:** Full voltage non-reversing mini contactor

Supporting documents:

- [Eaton's Volume 5-Motor Control and Protection](#)
- [XTMR AutoCAD 2D Footprint](#)
- [XTMR 3D Model Xchange](#)
- [XTMR AutoCAD 2D Footprint \(mm\)](#)
- [XTMR 3D Inventor](#)
- [XTMR 2D PDF](#)
- [XTMR 2D Drawing Xchange](#)
- [Eaton Specification Sheet - XTMR9A21A](#)



Certifications:

- CSA Certified
- UL Listed
- IEC 60947
- EN 60947

Product compliance:

- CE Marked
- RoHS Compliant

© 2016 Eaton. All rights reserved.