

## Eaton XT IEC contactor

XTCE065DS1T

UPC:786685443348

### Dimensions:

- **Height:** 1 IN
- **Length:** 1 IN
- **Width:** 1 IN

**Weight:**1 LB

**Notes:**Screw terminals (6-65A); 5 mm (80-150A);  
no lugs (185-2000A)

### Warranties:

### Specifications:

- **Amperage Rating:** 65A
- **Auxiliary Contact:** Side-mounted
- **Coil:** 24V 50/60 Hz
- **Coil Voltage:** 24 Vac, 50-60 Hz
- **Contact Configuration:** 1NO-1NC
- **Frame Size:** 55 mm
- **Frequency Rating:** 50-60 Hz
- **Max Hp Rating:** 5, 10, 15/ 20, 25, 50, 60 hp  
(1/3PH @115,200,230/200,230,460,575 V)
- **Number Of Poles:** Three-pole
- **Operation:** Non-reversing
- **Series:** XT IEC series
- **Terminals:** Screw terminals
- **Type:** Full voltage non-reversing contactor

### Supporting documents:

- [Eaton's Volume 5-Motor Control and Protection](#)
- [XTCE\\_D 2D PDF](#)
- [XTCE\\_D 3D Inventor](#)
- [XTCE\\_D 3D Model Xchange](#)
- [XTCE\\_D AutoCAD 2D Footprint](#)
- [XTCE\\_D 2D Drawing Xchange](#)
- [Eaton Specification Sheet - XTCE065DS1T](#)



**Certifications:**

- UL Listed
- IEC 60947
- CSA Certified
- EN 60947

**Product compliance:**

- CE Marked
- RoHS Compliant

---

© 2016 Eaton. All rights reserved.