STE302P
ELECTRONIC THERMOSTAT – MULTIPLE PROGRAMMING

3000 W

DESIGNED FOR:

PROGRAMMING IS CHILD'S PLAY!

Cost-saving programming, that's what the STE302P thermostat has to offer. Life just got simpler and more comfortable thanks to its "Pre-Prog" mode that allows you to easily and quickly program a temperature setpoint. Offering 18 preset programs, users can easily choose from the most common settings or program their own custom settings.

5-2 DAY PROGRAMMING

18 PREPROGRAMMING
INCLUDES 18 PRESET PROGRAMS IN "PRE-PROG" MODE

± 0.5 °C INCREASED SAVINGS AND COMFORT
INCOMPARABLE ACCURACY

ANTICIPATED START
REACH THE TEMPERATURE SETPOINT PRECISELY AT THE PROGRAMMED TIME

BACKLIT SCREEN
CAN BE USED AS A NIGHTLIGHT

ELECTRICITY SAVINGS
ENERGY SAVINGS OF 15-20% DEPENDING ON USE*

COLOUR
• white

FINISH
• molded plastic

WATTAGE AND VOLTAGE
• 150 W to 1500 W @ 120 V
• 260 W to 2600 W @ 208 V
• 300 W to 3000 W @ 240 V

CONTROL
• two- or four-wire connection
• compatible with forced-air units (Fan mode)
• easily choose the desired pre-programming with one button
• possibility of four events on week-days and four events on weekends
• anticipated start (the thermostat reaches the desired temperature at the requested time)
• frost-free warning

• lock option at a minimum and maximum temperature setpoint (Security mode)
• protection against power failure (two hours)
• time displayed in 12- or 24-hour mode
• display in Celsius or Fahrenheit

ACCURACY
• accurate ambient temperature control of ± 0.5 °C (1 °F)
• CSA C828-13
• temperature sensing with thermistor

TEMPERATURE RANGE
• 3 to 30 °C (37 to 86 °F)

WARRANTY
• three years
* Independent study

TECHNICAL SPECIFICATIONS

PRODUCT	WATTS		VOLTAGE	AMPERAGE	FREQUENCY	PACKAGING	UNIT PRICE
CODE	MINIMUM	MAXIMUM	VOLTS	AMPERES	HZ		
STE302PWB+	150/260/300	1500/2600/3000	120/208/240	12.5	50/60	BOX	44.00

DIMENSIONS: 4 7/8 in. (124 mm) wide, 4 7/8 in. (124 mm) high and 1 1/8 in. (29 mm) deep

°STELPRO