Energy Advantage IR PAR38

Energy Advantage IR 100PAR38/IRC+/FL25 120V

Due to the heat that radiates from the bulb, a minimum distance of 2 ft is required between bulb and combustible materials or objects susceptible to drying or fading

Product data

General Information	
Base	E26/50X39 [Skirted Medium Screw (PAR Lamps)]
Operating Position	Universal [Universal]
Main Application	Outdoor (OD)
Gas Filling	GAS

Light Technical	
Beam Angle (Nom)	25 °
Initial lumen (Nom)	2200 lm
Luminous Intensity (Nom)	8500 cd
Beam Description	Flood [Flood]
Correlated Color Temperature (Nom)	2900 K
Color Rendering Index (Nom)	100

Operating and Electrical	
Power (Rated) (Nom)	100 W
Voltage (Nom)	120 V

Mechanical and Housing	
Bulb Finish	Clear (CL)
Cap-Base Information	Brass [Brass Cap]
Bulb Material	Hard Glass
Reflector Finish	Aluminized
Filament Shape	CC-8 [Axial]

Product Data	
Order product name	Energy Advantage IR 100PAR38/IRC+/FL25 120V
EAN/UPC - Product	046677138776
Order code	138776
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	12
Material Nr. (12NC)	924757119572
Net Weight (Piece)	370.000 g

Energy Advantage IR PAR38

Dimensional drawing



PAR38 IRC 100W E26/50x39 120V FL 25D

Product	D	C (max)
Energy Advantage IR 100PAR38/IRC+/FL25 120V	4.75 in	5.313 in

© 2018 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.